

Manufacturer	Item	Description
Cameras		
Fujifilm	X-S1	
Grass Valley	AMU	
Grass Valley	CCU 8000 Triax	Base Station for LDK 8000
Grass Valley	Wireless HD-Camerasystem	
Grass Valley	Eyecatcher 744 7" OLED Sucher	
Grass Valley	Eyecatcher EC200	2" viewfinder
Grass Valley	Eyecatcher EC744	7,4 viewfinder with sunhood small
Grass Valley	Grass Valley Microphone Clamp 3922 407 62711 (LDX 86N)	
Grass Valley	Large Lens Adapter LDK 4488 f	for LDK8000
Grass Valley	Large Lens Adapter LDK 4488	for LDK8000
Grass Valley	LDK 23P - MK-II	Super slow motion camera package without lense
Grass Valley	LDK 4016/02	7" viewfinder
Grass Valley		
Grass Valley	7" HDTV Viewfinder LDK 4021	for Large lens adapter
Grass Valley	LDK 4482	Large Lense SuperXPander
Grass Valley	LDK 4482 D&H	Large Lens Adapter
Grass Valley	LDK 4487/06 Triax connection cable for LLA	Triax connection cable for LLA
Grass Valley	LDK 4487/61 Glasfaseranschluß für LLA	
Grass Valley	7" HDTV Viewfinder LDK 4021	for Large lens adapter
Grass Valley	LDK 5305 Viewfinder	5" black & white
Grass Valley	7" HDTV Viewfinder LDK 5307	for Large lens adapter
Grass Valley	LDK 5310, 5" Viewfinder	
Grass Valley	LDK 8000 Camera-Package (Triax)	incl. Camera Head, Triax Adapter, 2" & 5"Viewfinder, Base Station (CCU), Remote Control Unit (OCP 400)
Grass Valley	LDK 8000 Camera-Package (SMPTE 311)	incl. Camera Head, Fibre Adapter, 2" & 5"Viewfinder, Base Station (CCU), Remote Control Unit (OCP 400), Headset, Rain Cover
Grass Valley	LDK 8300 SSL camera system	SSL Camerasystem with LDK 4475 Large Lens Adapter, 7" b/w HD viewfinder, CCU LDK 4430. OCP 400 and raincover
Grass Valley	LDX 80 Camera Package (Triax)	LDX 80 Premiere camera head, LDX 5640 triax adapter, LDK 5031 tripod adapter plate, 2" and 7" viewfinder, XCU 4270 Basestation and OCP 400
Grass Valley	LDX 86 XS SSL HD camerahead	incl. Camerahead LDX 86 XS, XS Fiber Adapter Lemo, 3G Super Expander, 7,4" OLED viewfinder, CCU XCU XS Lemo, OCP 400 and raincover
Grass Valley	LDX 86N Worldcam UHD Camerasystem	UHD camera, incl. tripod adapter plate, XCU Universe XF Basisstation, OCP 400 Control Panel, Eyecatcher EC744, Eyecatcher EC200
Grass Valley	LDX 86N Worldcam UHD Camerasystem (HDR eLicence + SSL License)	UHD camerahead, incl. tripod adapter plate, XCU Universe XF Basisstation, OCP 400 Control Panel, Eyecatcher EC744, Eyecatcher EC200
Grass Valley	MCP 400	Master Control Panel
Grass Valley	OCP 400 / LDK 4640	Remote Control Unit for LDK 8000
Grass Valley	OCP 400 Control Panel	Operation Control Panel, incl. Power Supply
Grass Valley	Reflex Super Expander LDK 4475/15	with Vinten Wedgeplate
Grass Valley	Sunhood/Fieldhood LDK 6992/12	
Grass Valley	XCU Universe XF Basestation	for LDX 86N with Network-, Tally and Intercom cables
Grass Valley	XF Universe Adapter	Lemo Fibre Adapter LDX 86N
HD Wireless	Wireless Camera System	Model 1609 for HDC 2400 / 2500. Camera-side-cover with integrated transmitter for Video und telemetry, 2/3 & 7 GHz. incl. Basestation
Nikon	D4	Single lens reflex digital camera
Panasonic	AW-HE120KE Video camera with pan/tilt head	HD Integrated Pan/Tilt Camera with 20x zoom lens.

Manufacturer	Item	Description
Panasonic	AW-HE130KE Video camera with pan/tilt head	The AW-HE130 is the successor to the proven AW-HE120. The Full HD camera with integrated pan-tilt function offers advanced features for a wide range of applications. Thanks to three newly developed 1/2.86 megapixel MOS sensors, the AW-HE130 is suitable for high-quality filming - even in low-light conditions. It also offers an excellent signal-to-noise ratio and high resolution. In addition to 3G-SDI and HDMI video output, the Panasonic camera also supports the output of full HD video in production quality via IP transmission. With configuration levels of the appropriate quality level, the camera enables IP streaming of video (H.264) on up to four channels. The
Panasonic	AW-RM50	Wireless Remote Controller for AW-HE120KE
Panasonic	AW-RP120 Camera Controller	Remote PTZ Camera System Controller with IP and Serial Connectivity
Panasonic	AW-RP150GJ	Kamera-Steuereinheit für PTZ-Kameras intuitive Kamerasteuerung großes 7"-Touch-Display für schnelle Bedienung aller Kamerafunktionen integrierter Wippschalter am Joystick für Zoom-/Fokussteuerung per Ein-Hand-Bedienung Vereinfachte Preset-/Tracing-Speicherfunktionen für die PTZ-Kamera 3G-SDI Active Through Output, 5 x RS-422, LAN PoE+, 2 x GPIOs
Panasonic	AW-RP60GJ	Remote Camera Controller neuer Joystick unterstützt eine weiche Schwenk-, Neige-Steuerung 3,5" LCD GUI-Bildschirm 4 benutzerdefinierbare Tasten für bis zu 8 Funktionen PoE-Unterstützung / Erweiterte Kameraeinstellungen 1x Tally/GPIO-Schnittstelle Steuerung von bis zu 200 Kameras über LAN Optimierte Tastenanordnung für Bediener
Panasonic	AW-UE150KEJ	4K Schwenk-/Neige-Kamera mit HDMI, 12G-/3G-SDI 1 Zoll MOS Sensor 4K (3840 x 2160) Ausgabe 59.94p 12G-SDI, 3G-SDI, HD-SDI, HDMI, IP, Glasfaser Ausgänge 20x Zoom (Optisch) 75,1° Horizontale Weitwinkelaufzeichnung Ausgabeformate: 4K: 2160/59.94p, 2160/50p, 2160/29.97p*, 2160/25p*, 2160/24p*, 2160/23.98p* HD: 1080/59.94p, 1080/50p, 1080/29.97p*,
Panasonic	Planet POE-171A-95 Injektor	Single-Port Multi-Gigabit 802.3bt PoE++ Injector (95 Watts)
SONOVTS	Scripholder with light	
Sony	BPU 4000 4K Base Band Processor Unit	The BPU-4000 works with the HDCU-2000/2500 to permit the same system operation as the current HDC camera system.
Sony	CNA-1 Network adapter for camera control	
Sony	HDC 1500 camera channel	include HDVF-20 Viewfinder, HDVF-C730/750 7"-Viewfinder, HDCU 1000/1500 CCU, RCP-750, Remotecabel und Mounting plate
Sony	HDC 3300	HD-Super-Motion Camerasystem
Sony	HDC-1500OLED Camera Channel	
Sony	HDC-2500 camera channel	3G Double-Speed-Multi-Format HD-System-Camera, incl. HDCU 2500, 2" Viewfinder, RCP 1500, 7.4" OLED Color-Viewfinder, Mountingplate, Headsets (1-ear, 2-ear)
Sony	HDC-4300 Camera System	Multi-Format 3G HD-System-Camera, incl. HDCU 2500, BPU4000, 2" Color - Finder, 7.4" OLED Color - Finder, RCP 1500, Mounting-plate, Headset (1x Stereo, 1x 1 mono)
Sony	HDC-4300 Camera System, UHD License	Multi-Format 3G HD-System-Camera, incl. HDCU 2500, BPU4000, 2" Color - Finder, 7.4" OLED Color - Finder, RCP 1500, Mounting-plate, Headset (1x Stereo, 1x 1 mono), UHD Output via 4 x BNC
Sony	HDC-4300 Camera System, SSL License	Multi-Format 3G HD-System-Camera, incl. HDCU 2500, BPU4000, 2" Color - Finder, 7.4" OLED Color - Finder, RCP 1500, Mounting-plate, Headset (1x Stereo, 1x 1 mono), up to 8 x HD Super Slow Motion
Sony	HDCU 2500	Compact fibre CCU for HDC-2500 high definition camera
Sony	HDCU-1000	Fibre CCU designed for HDC-1500 high definition camera
Sony	HDCU-1500	Compact fibre CCU für HDC-1500 high definition camera
Sony	HDLA-1505	large lens adapter

Manufacturer	Item	Description
Sony	HDVF-200	2inch HD Viewfinder for all Sony 2/3" HD Cameras
Sony	HDVF-700A	7" viewfinder
Sony	HDVF-EL20 viewfinder	
Sony	HDVF-EL75 OLED Color Viewfinder	7,4-inch OLED Color Viewfinder
Sony	HKCU/2007	Sony 3G/HDSI OUTPUT EXPANSION
Sony	PMW-200	HD-SDI Camcorder
Sony	PMW-F3	HD-SDI Camcorder, 2 x SxS-Flashcard Slots, incl. Lenses SCL-P35/50/85T20, incl. Accessories (Batterie, Batterie-Charger, Card-Reader ... etc.)
Sony	RCP 750	Remote panel for HDCU-1000/1500/3300
Sony	RCP 750	Remote panel for HDCU-1000/1500/3300
Sony	RCP-1500	Remote Control Panel for HDC/DXC Camera
Vislink	L1700 Camera Transmitter	HD H.264 Very Low Latency Encoder HD/HDMI/Composite Input, up to 1080i/60, incl. Telemetry Receiver
Vislink	L2194 Receiver/Decoder	HD H.264/MPEG-2 Receiver / Decoder Incl. Quad - Diversity Option, up to 1080i/60
Zacuto	Z-EVF-IF	3,2 high resolution Viewfinder, LCD Panel, HDMI (with Loop Through) input

Lenses

7inch	Rain-and Dustcover	colour black, in grey transport bag
7inch	raincover 7inch OB studio	for box lenses, in blue transport bag
CamRade	rain cover WS OB Studio	for 55/70/86/100-fach lenses
Canon	CJ12ex4,3B IASE-S	4K Super Wide angle lens
Canon	CJ14ex4.3B IASE-S	4K Wideangle
Canon	CJ25ex7,6B IASE S 4K	4K Zoom-lens
Canon	HJ 11x 4,7BIASE	11x HDTV Superwideangel-Zoom lens
Canon	HJ14x4,3BIASE	wideangle lens + UV Filter
Canon	HJ22x7,6BIASE	ENG lens
Canon	HJ40x10 BIASD	40x HD Zoom-Lens
Canon	J 33a x 15 BIAS	ENG zoom lense
Canon	J 50 x 9,5 BIE	
Canon	J 55 x 9BIE	55x Super Box lense, Fullservo with focus demand
Canon	PJ55 x 9 BIE	55x Super Box lense Fullservo (Sony Mount), with focus demand
Canon	PJ70x9,5BIE (SD)	70x Digi-Super Lens full servo
Canon	SS-41-IASD remotes	Digital Zoom & Focus Control
Canon	Supporter SUP-NS3	
Canon	UJ111x8.3B 4K	Box Lens (4K) with Full servo zoom and focus controls
Canon	UJ90x9B DIGISUPER 4K	Box Lens (4K) with Full servo zoom and focus controls
Canon	XJ100x9,3 BIE-D	Box Lens (HD) with Full servo zoom and focus controls
Canon	XJ27x6,5 B	Box Lens
Canon	XJ60x9 BIE-D	Box Lens (HD) with Full servo zoom and focus controls
Canon	XJ72x9,3 BIE-D	Box Lens (HD) with Full servo zoom and focus controls
Canon	XJ75x9,3BIE-D	HDTV box lens with full servo remotes
Canon	XJ86x9,3 BIE-D	Box Lens (HD) with Full servo zoom and focus controls
Canon	XJ95x8,6 BIE-D	Box Lens (HD) with Full servo zoom and focus controls
Fujinon	Fujinon AH-70x	Fujinon AH-70x Box lens kit Ah 70 x 1:1.6/9.5-665 with Full servo zoom and focus controls.
Fujinon	HA 22x7.3BROS48/SS-130-FIN	HD-ENG Lens + UV-Filter with digital Zoom & Focus Control
Fujinon	HA13x4,5BROS58/SS-130-FIN	HD-ENG Lens + UV Filter with digital Zoom & Focus Control
Fujinon	HA14x4,5BERD	HD-ENG Lens + UV Filter with digital Zoom & Focus Control
Fujinon	HA18x7,6BERM/BERD	2/3" HD-Standartzoom ENG T1,9/ 18x7,6mm (7,6-136mm) EXT, Makro, BI, B4
Fujinon	HA42x9,7BERD-U	HDTV ENG Tele-Objektiv 9,7-410 mm, 42-x Zoom with digital Zoom & Focus Control

Manufacturer	Item	Description
Fujinon	XA101x8,9BESM-S16B	box lens
Fujinon	XA72x9,3BESM D16C	Box Lens with full servo remotes
Fujinon	XA87x9,3BESM-S16B	HDTV box lens full servo
Sony	CC/LDK200 rain cover	for 55/70/86/100x lenses
Vision Mixers		
	ICP-X7000	Vision Mixer Panel incl. Modul
Guntermann & Drunck	UCON Workplace module	Workstation-End-Module
NewTek	NewTek, TriCaster TC1 DELUXE Bundle video mixer	TriCaster TC1 R3, NC1 I/O and TC1LP control panel
Panasonic	AV-HS 450 E	SD/HD-SDI Visionmixer, 16 HD/SD-SDI Inputs (Standard) und optional DVI und FBAS. Compact 2HE Mainframe and Remote-Panel, internal Multiviewer max. 20 in 2
Sono	Tally Bauträger	
Sony	CCP-8000	
Sony	ICP-3000	Remote Panel for MVS-3000
Sony	ICP-6511	Menu Panel for MVS-3000
SONY	MKS X 2700-C	System Interface Unit
Sony	MKS-2700	Device Control Unit for Sony MVS Switchers
Sony	MKS-8010B	System Control Unit for Sony MVS Panel
Sony	MKS-8011A	
Sony	MKS-8013A	
Sony	MKS-8076	
Sony	MKS-8082	
SONY	MKS-X7011	Menue Panel Vision Mixer
Sony	MVS 3000	HD-SDI Vision Mixer, 32 Inputs, 16 Outputs, 24-Key Control Panel, 4 Keyer 2 ME, -splittable into 4 ME, 2 integrated Multiviewer, 2 Channel internal 3D DME, 2.5 DME Resizer und Chromakey per M/E, Color Correction for all Inputs and AUX Outs, Formatconverter Board with 8 Inputs and 2 Outputs up to 8 Frames Delay, (up/down conversion HD (1080i/720p) to SD (480i/576i), cross (1080i und 720p)
Sony	MVS-7000X	80 Inputs, 48 Outputs, 2 M/E Boards each with 8 Keyern and M/E Split, e.g. 4M/E, each 4 Keyer at 1080i, (at 1080p the half of it, so then 2 ME bei 1080p with 4 Keyer), 2.5D DME Resizer and Chromakey per Keyer, 2 3D internal DME Channels, 2 Integrated Multiviewer with 4 oder 10-way split screen, Formatconverter Board with 8 Inputs / 4 Outputs and 8 Frames Delay, (up/down conversion HD (1080i/720p) to SD (480i/576i), cross (1080i and 720p), Frame Synchronizer
Sony	PFV-SP3100 with HKSP-R80/81	The HKSP-R80 routing switcher controller is a stand-alone primary station CPU board for Sony routing switchers. The HKSP-R80 fits in a PFV-SP Series signal processing unit. The HKSP-R80 provides a range of features in addition to the primary functions of S-BUS SUB-NET control and conversion between S-BUS and Ethernet LAN. For CPU redundancy, the HKSP-R81 is available as a backup to the HKSP-R80. Installs in PFV-SP Series Signal Processing Units in any combination with other HKPF-SP/HKSP function boards.
SONY	PWS-110SC1	Worklow Station
Sony	Sony MVS-8000G	HD-SDI Vision Mixer, 34 Inputs, 24 Outputs, 24-Key Control Panel, 24-Key Aux Panel, Multi-Format DME Processor
SONY	XVS-7000	Der Multiformat-Vision-Mixer, 6 M/E-Busses, 112 Inputs, 48 Outputs, up to 24 Keyer in HD. Ugradeable to 4K.
SONY	XVS-8000	4K-Mixer, 4K-Funtions similar to HD-Productions, 5 M/E-Busses, 40 Inputs, 12 Outputs in 4K, up to 10 Keyer and 10 Sub-Keyer, synchronous 4K- und HD-Mode

Manufacturer	Item	Description
Integrated Systems		
sonoVTS	40 ' Equipment Room Container	high cube shipping container. 17 x 19" Racks, 45 RU inside. Shockproved mounted, access floor construction for cableing, Air condition mounts, entrance-tent
sonoVTS	mobile production KIT	video-& audio router, vision mixer, audio mixer, intercom, IT, cameras, glue & processing, power, etc., are fully wired and available in stackable racks.
sonoVTS	MPK Rack Audio	
sonoVTS	MPK Rack Audio Stagebox	
sonoVTS	MPK Rack AUX (large)	
sonoVTS	MPK Rack AUX (small)	
sonoVTS	MPK Rack Vision Mixer (large)	
sonoVTS	MPK Rack Vision Mixer (medium)	<ul style="list-style-type: none"> - 1x Sony MVS-3000A (2 M/E mit je 4 Keyern, 32 Inputs, 16 Outputs, Formatconverter, 2 Kanal 3D-DVE, integrierter Multiviewer, incl. Tally-Auflösung - 1x Sony HKSP-R80 S-Bus Interface - 2x Netgear Ethernet Switch
sonoVTS	MPK Rack Intercom (large)	
sonoVTS	MPK Rack Intercom (medium)	Digital, Riedel Artist 64 with red. Controller, COAX, AIO as requested
sonoVTS	MPK Rack IT (large)	
sonoVTS	MPK Rack IT (small)	<ul style="list-style-type: none"> - 2x VSM Server (HP ProLiant DL360 G7), - 2x Magellan Server (wird für Imagine IP3 DVKS benötigt) - 2x Config-PC (XEON, 16GB RAM, SSD, Grafik, Win7) - 1x G&D KVM Matrix 32x8 Port - 2x Netgear Ethernet Switch
sonoVTS	MPK Rack Camera (large)	Up to 8x Sony HDCU-2500 Internal Distribution for Reference/Return 1&2-Video/Intercom/PGM-Audio, VSM GPI Interface, Tally-GPI/Intercom-Audio/PGM-Audio/Preview-GPI Patch, Cisco 48 Port Switch (24U Rack)
sonoVTS	MPK Rack Camera (small)	
sonoVTS	MPK Rack Kamera (medium)	<ul style="list-style-type: none"> -Bis zu 4x Sony HDCU-2500 incl. 4x Sony BPU-4000 (max.) - 1x Integrierte RCP Schublade - 1x Tektronix WFM-5000 - 1x Integrierte Display (Kamerakontrolle) - 1x Verteilung für Takt, Return 1&2, HD Prompter, Intercom, PGM-Audio - 1x Netgear PoE Ethernet Switch -1x Intercom Panel -1x KS 32x32 Nevision mit GPI -1 Telebrücke für 4x Kamera PVW
SONOVTS	MPK Rack Power Distribution (small)	
SONOVTS	MPK Rack Power Distribution (medium)	<ul style="list-style-type: none"> - 2x Connex Unterverteilung 32A CEE auf 12 Schuko & PowerCon True - 2x Power Analyzer PWM-304
sonoVTS	MPK Rack SPG (large)	
sonoVTS	MPK Rack SPG (small)	<ul style="list-style-type: none"> - 2x Tektronix SPG8000 Taktgenerator - 1x Tektronix ECO8000 Auto-Changeover - 1x TLS-Verteiler (24 Port) - 1x BB Verteiler (24 Port) - 1x LTC Verteiler (8 Port) - 1x HD-Bars & HD-Black Verteilung (je 8 Port) - 2x GPS-Antennen
sonoVTS	MPK Rack Video Stagebox TX/RX Bundle	Bundle includes 2 Racks (RX and TX) Yellobriks in RFR Frame with red. Power Supplies, 12x Video Channels (10x TX and 2x RX), 1x Network, 1x Sync (BB or TLS, CWDM Multiplexing on 4x Singlemode Fiber, Neutrik OpticalCon Quad Connectors
sonoVTS	MPK Rack Video Router (large)	<ul style="list-style-type: none"> - 1x Imagine Platinum IP3 Mainframe - 2x Imagine Platinum IP3 Crosspoint Karte - 2x Imagine Platinum IP3 Ressource Controller Karte - 2x Netgear Ethernet Switch - Bestückung nach Bedarf
sonoVTS	MPK Rack Video Router (small)	

Manufacturer	Item	Description
sonoVTS	MPK Rack Video Router (medium)	Imagine Platinum Router, red. Power-supply/Crosspoint-/Controller, 128 x 128 Matrix, incl. 2x Imagine Platinum SX-Pro 32x6 Multiviewer, Multiformat SD/HD/3G, Cisco 48 Port Switch (10HE Rack)
sonoVTS	MPK Table (1 Operator, small)	
sonoVTS	MPK Table (2 Operators)	Workspace for 2 Persons Incl. 2x 5U Tableracks
sonoVTS	MPK Table Vision Mixer (large)	
sonoVTS	MPK Table Vision Mixer (medium)	Workspace for 2 Persons Incl. Main/Menu-Panel-VESA-Displaytray
sonoVTS	MPK Table Shading (large)	Workspace for 2 Persons Incl. 2x 2Z Tischracks Up to 11x Sony RCP-1500
sonoVTS	MPK Table Shading (small)	

Video - Recorder / Player

AJA	HELO H.264 Streamer & Recorder	SDI and HDMI input/output into a single appliance with the ability to simultaneously stream out to your Content Delivery Network (CDN) as well as encode and record H.264 files to SD cards, USB storage, or network-based storage simultaneously.
AJA	KiPro mini	Compact Flash Field Recorder, HD-SDI / SDI and HDMI Inputs
AJA	KiPro Rack	1RU Hard Disk Recorder - HDSDI, HDMI, Component, AES Audio, Analogue Audio in/out - Apple ProRes/Avid DNxHD Codec - 2 HDD Slots
AJA	KiPro Ultra	4K/UltraHD and 2K/HD Recorder and Player
AJA	KISTOR750 USB-RO	750GB HDD storage module with USB3.0
AJA	KiStor Dock	External Dock for KiStor Storage Modules w/ Thunderbolt and USB3
AJA	Pak	Pak with 256GB
AJA	Pak Dock	
Apple	TV 4K 32GB	-4K High Dynamic Range (Dolby Vision and HDR10) for stunning image quality -Dolby Atmos for three-dimensional, room-filling sound -A10X Fusion chip for ultra-fast graphics and performance -Search by voice with the Siri Remote remote control -Use AirPlay to view photos and videos from your iPhone or iPad on your TV -Netflix, Sky Ticket, TV Now Plus, Amazon Prime Video, iTunes and thousands of more apps in the App Store
Audio Development	AD 261	stereo-EB-mixer , 4-ch.
Audio-Service		
Blackmagicdesign	Hyper Deck Studio Pro 4K	Incl SSD Disk Hyper Kingston 480 Gb
Blackmagicdesign	HyperDeck Shuttle 2	mobile SSD Recorder, DNxHD and uncompressed HD on SSD Disk.
Dan Dugan	Model E-3	Automatic Mixing Controller, AES Digital
HHB	UDP-89	professionell DVD Player, discrete 5.1 Outputs (Cinch und balanced), AES/EBU Stereo, HDMI, Composite, ,RGB S-Video, CVBS, encode Dolby/DTS via SPDIF optical and coax, RS232, Parallel Remote
Lawo	mc² 56 MKII 16/16C/16 Mixing console (available as of October)	16/16C/16 Frame, 32 fully Channelstrips, 16 short Channelstrips, 144 DSP Channels, 1x HD-Core + red. Controller, 3 Dallis Frame Inkl. Case
LGZ	H.264 USB Recorder	This USB Recorder can take in 1 HD/SD-SDI input with 2ch embedded audio and record it live on 8 USB sticks simultaneously. All in high quality H.264! (AES audio and analogue video with the Decklink Studio option)
Lynx	Yellobrik PEC 1864 Streamer and Recorder	3Gbit SDI/HDMI H.264 Streamer and Recorder
Mackie	1402	6 mono mic/line / 4 stereo line/ 1 tape L/R/ 2 stereo aux returns/ aux 1x pre-fader - 1x post- fader
Midas	PSU	power supply unit
Midas	XL4 Mixing console	mixer 48 / 16 / 24 / 8 / 2 / 2 / 2 / 1

Manufacturer	Item	Description
Panasonic	AG-HPD24EJ	portable P2HD Recorder, Stereo 3D, Record/Play: AVC-Intra 100/50, DVCPRO50, DVCPRO und DV, Video In: 2 x HDS DI, Video Out: 2 x HDS DI, 1 x HDMI, 1 x composite
Panasonic	AJ-HD 1400	DVCPRO HD Recorder
Panasonic	AJ-HD1700E	DVCPRO Recorder
Panasonic	AJ-HPS 1500	Panasonic P2 HD recorder
Panasonic	Panasonic AU-XPDI	
Riedel	AES67-108 G2 SET Artist AES67 Client Card Set	Converts 8 Artist Matrix AES ports to unidirectional AES67 streams and vice versa. The client card can connect to other AES67 client cards or with intercom stations. The set consists of an AES67 rear card and front card: 2xRJ45AES67 Ethernet 100 0Base-T; 1xRJ45 ETH 100Base-T; 1x BNC Wordclock Out
Riedel	GigaCore 12 Switch (LU 01 00036-POE) 12-port, PoE+	Transfer multiple protocols (Dante™, RAVENNA/AES67®, ArtNet, MANet 1&2, sACN, Q-LAN ...)
Riedel	NSA-002A 4-Wire & GPIO Interface Box	Rugged 4-wire box with 6 analogue inputs and 6 analogue outputs 3 GPI-In, 3 GPI-Out AES67 Layer 3 IP network via a CAT-5.cabling internal universal power adapter SPK-001 - Stagebox Protection Kit included can be used as a throwdown box
Shure	SCM 810 intellimix	8-ch. automatic-mixer
sono	3-inputs-summing amplifier	
Sony	Digibeta DVW-A500P	DigiBeta Recorder
Sony	DVW A500P	Digital Betacam Recorder
Sony	DVW-500	Digital-Betacam Recorder
Sony	HDW-2000P	HDCAM Recorder
Sony	HDW-D1800	HDCAM VTR, Multi-Format Playback: HDCAM (1080/50i, 59,94i, 25P, 29,97P, 23,98P, 24P) Digital Betacam, MPEG IMX,
Sony	HDW-D2000P	HDCam Recorder
Sony	HDW-M2000P/20	HDCAM VTR, Multi-Format Playback: HDCAM (1080/50i, 59,94i, 25P, 29,97P, 23,98P, 24P) Digital Betacam, MPEG IMX, Betacam SX, Betacam SP, Betacam
Sony	J-30SDI player	Digibeta, Beta SP, Beta SX, IMX, - Player
Sony	PDW-F1600	XD-Cam HD422 Recorder
Sony	PDW-HD1500	XD-Cam HD422 Recorder incl. SD-Option
Sony		XDCam-drive for Professional Discs
Sony	RM-280	Editing controller, for two-machine VTR
Sony	SBAC-US10	SxS Memory Card USB Reader/Writer
Sony	SRW-5800 HD-Cam SR Recorder	
Studer	DM 2000	digital mixer, 96 inputs in 4 layers
WorkPro	MD 82 AX MKII mixer for microphone	8-channel auto microphone mixer. Control RS485. Bluetooth
Yamaha	01V96VCM Mixing console	Digital mixer, 16 faders, card slot for MY interface cards,
Yamaha	02R96V2	digital mixer, 96 inputs in 4 layers
Yamaha	CP4SF	Control Panel w. Fader
Yamaha	CP4SW	Controller Panel
Yamaha	DM 1000 V2	digital mixer, 48 inputs in 3 layers, internal Effects
Yamaha	DM 2000 V2 VCM	digital mixer, 96 inputs in 4 layers, internal VCM effects inkl. flightcase
Yamaha		
Yamaha	MG 16/6 FX Mixing Console	analogue 16 channel mixing console, Digital Effects Section
Yamaha	MG 166C-USB Mixing Console	analogue 16 channel mixing console with USB Interface
Yamaha	MY16-AUD	16 Channel Dante-Audio-Network Interface for Yamaha Consoles
Yamaha	MY16-Dugan	16-channel automatic mixing controller that plugs into a slot on Yamaha consoles
Yamaha	MY16-EX	
Yamaha	MY16AE mini-YGDAI card	16 way AES in/out interface
Yamaha	MY16AT mini-YGDAI card	16 way ADAT interface
Yamaha	MY16C	16-Ch CobraNet interface für DME24N/DME64N/PM5D/DM2000V2 - 2x RJ45 terminals

Manufacturer	Item	Description
Yamaha	MY8-ADDA96	8x Analog IN, 8x Analog OUT
Yamaha	MY8AD mini-YGDAI card	8 way analog input interface
Yamaha	MY8AD96 mini-YGDAI Karte	8 way analog input interface
Yamaha	MY8AE mini-YGDAI card	8 way AES interface
Yamaha	MY8AT mini-YGDAI card	8 way ADAT interface
Yamaha	MY8DA96 mini-YGDAI card	8 way analog output interface
Yamaha	MY8TD mini-YGDAI Karte	8 way TDIF interface card
Yamaha	QL1	Audio-Mixing consoles, 32 mono, 8 stereo. Busses: 16 mix, 8 matrix (Input to Matrix supported). Local I/O: 16 in, 8 out. Fader configuration: 16 + 2 (Master).
Yamaha	QL5	32 + 2 Fader , 64 mono, 8 stereo Mix channels, 16 mixBusses, 8 matrix, Local I/O: 32 in, 16 out. Fader configuration: 32 + 2 (Master)
Yamaha	MY16-EX	Madi Card
Intercom - Wireless -Analogue		
Motorola	2 unit charger	
Motorola	Visar portable radio	TX/RX frequenzies: 419,86250, 429,86250, 466,150, 466,030
Motorola	Akku für GP344	
Motorola	Clips für GP 344	
Motorola	DP4400	
Motorola	DP4800	
Motorola	radio case	6 x VISAR radios incl. headsets 6 x backup accus 6-unit charger
Motorola	GP344 portable radio	incl. light-weight Headset, Batterie, Batterie-charger,
Motorola	headset für Visar (light)	
Motorola	MDPMMN4023A	
Motorola	SLR 5500	
Motorola		
Motorola		
Pastega (baugleich Wisycom)	RST 12 beltpack	446-467 MHZ, 16 selectable frequencies incl. headset
Pastega (baugleich Wisycom)	TSC37 (1) / RSM 35 (1) basestation 1-ch.	470-494 MHZ, 16 selectable frequencies
Phonak	TX-300V	for Phonak Invisity Receiver
Riedel	Ri-face	2-ch. RF base-station with 4-wire port, incl. 2 antennas 410 - 470 MHz
Sennheiser	EK 3052	in-ear-monitor receiver
Sennheiser	EK 3052	in-ear-monitor receiver
Sennheiser	EK 3053	in-ear-monitor receiver, stereo
Sennheiser	SR 3054-U	in-ear-monitor transmitter
Wisycom	CPR 29	IFB beltpack receiver
Wisycom	CRT14/470/2T beltpack TX: 465-470 MHz RX: 445-450 MHz	TX: 465-470 MHz RX: 445-450 MHz, 16 selectable frequencies, 2 individual TX-frequencies in direct access
Wisycom	CRT16/470/2T beltpack TX: 465-470 MHz RX: 445-450 MHz	TX: 465-470 MHz RX: 445-450 MHz, 16 selectable frequencies, 2 individual TX-frequencies in direct access
Wisycom	CRT16/2T Beltpack	TX: 467-472 MHz RX: 453-458 MHz, 16 selectable frequencies, 2 individual TX-frequencies in direct access incl. headset
Wisycom	CSR 50 Receiver Module 467-472 MHz	
Wisycom	CSR 50 Receiver Module 465-470 MHz	for installation in Wisycom 3U rack frame
Wisycom	CST 38 transmitter for mikro-ear VHF	for Phonak Invisity Receiver, 212 - 221 MHz or 214 - 224 MHz
Wisycom	CST 50 Transmitter Module 445-450 MHz	
Wisycom	CST 50 Transmitter Module 453-458 MHz	

Manufacturer	Item	Description
Wisycom	FAS 16 Active Antenna Splitter Module 461	-466 MHz
Wisycom	FAS 16 Active Antenna Splitter Module 465	-470 MHz
Wisycom	RST 22-S Rackframe 8 Bay	
Wisycom	RST Rackframe 3 Bay	
Wisycom	RST Rackframe 4 Bay	
Wisycom	RST22 basestation	446-467 MHz, for 4 beltpacks, 2 TX- / 16 RX- selectable frequencies incl. antenna-splitter, antennas, sonifex matrix

Headsets - Accessories

AkG	DT 109 SB	for extreme loud ambience
Beyer Dynamic	Headset DT 108 2-Ohr XLR5/M	headset, dynamic microphone, cardioit
Beyer Dynamic	Headset DT 108, 5-pol XLR-Stecker	headset, dynamic microphone
Beyer Dynamic	Headset DT 109 2-Ohr, 5-pol XLR/M	headset, dynamic microphone
Beyer Dynamic	Headset DT 280 1-Ohr XLR3M / 6,3 Jack plug	headset, condenser microphone.
Beyer Dynamic	Headset DT 280 1-Ohr XLR5/M	headset, condenser microphone.
Beyer Dynamic	Headset DT 284 1-Ohr XLR3M / 6,3 Jack plug	headset, condenser microphone.
Beyer Dynamic	Headset DT 284 1-Ohr XLR4/F	headset, condenser microphone.
Beyer Dynamic	Headset DT 287 1-Ohr XLR5/M	headset, condenser microphone.
Beyer Dynamic	Headset DT 290 2-Ohr XLR3M / 6,3 Jack plug	headset, dynamic microphone, cardioit
Beyer Dynamic	Headset DT 290 2-Ohr XLR5/M	headset, dynamic microphone, cardioit
Beyer Dynamic	Headset DT 291 2-Ohr PV Motorola für GP344	
Beyer Dynamic	Headset DT 291 2-Ohr PV XLR3M / 6,3 Jack plug	
Beyer Dynamic	Headset DT 291 2-Ohr PV XLR5/M	
Beyer Dynamic	Headset DT 297 2-Ohr PV Fischer 5pol (Wisycom)	
Beyer Dynamic	Headset DT 297 2-Ohr PV XLR3M / 6,3 Jack plug	headset, condenser microphone, cardioit
Beyer Dynamic	Headset DT 297 2-Ohr PV XLR4/F	
Beyer Dynamic	Headset DT 297 2-Ohr PV XLR5/M	
Beyer Dynamic	Headset DT 797 PV XLR3M / 6,3 Jack plug	headset, condenser microphone, cardioit
Imtradex	Headset Buisnessline XS	Headset, monaural, light-weight, electret-Mic
Imtradex	Headset Buisnessline XS	Headset, monaural, light-weight, electret-Mic
Imtradex	Headset Buisnessline XS XLR 4Pol/F	Headset, monaural, light-weight, electret-Mic
MB Quart	K 800E, 1-Ohr pol XLR/F	
MB Quart	K 800 E, 5-pol XLR/M	
MB Quart	K 800 E	headset, single-ear, 5-pol DIN connector for 4000er Drake panels
MB Quart	K 800 headset	headset, dynamic microphone
MB Quart	K 800, XLR 4pol /F	
MB Quart	K 800E, 1Ohr pol XLR/F	
MB Quart	K 800 E 2-Ohr, 5-pol XLR/M	
Motorola	JMMN4066A, lightweight heaset for GP344 radio	
OTTO	heavy duty headset Fischer 5pol	for extreme loud ambience
OTTO	heavy duty headset XLR 4pol/F	for extreme loud ambience
Otto	"security"- headset TS1/P/Visar	miniature headphone, miniature microphone, PTT button on cable
Peltor	MT7H79A-04 XLR5M	

Manufacturer	Item	Description
Riedel	AIR-E1 (XLR4F)	Ultra-lightweight 1-ear headset; can be worn on the right or left; high wearing comfort; electret microphone (bidirectional); connection cable (4-pole XLR female)
Riedel	MAX Headset Fischer 5pol	for extreme loud ambience
Riedel	MAX Headset XLR 4pol/F	for extreme loud ambience
Riedel	MAX-D1 Headset XLR3/M / 6,3 Jack plug	for extreme loud ambience
Riedel		
Sennheiser	HD-25	Headphone
Sennheiser	HMD 410	headset, condenser microphone, lightweight
Sennheiser	HMD 25 headset	headset, dyn. hyper cardoid
Sennheiser	HMD 26 Headset, XLR 4pol/F für Riedel/Clearcom	headset, dyn. hyper cardoid
Sennheiser	HMD 26-II-100 mit XLR3M / 6,3 Jack plug	Headset, 100 O per system, dynamic microphone, supercardioid, with XLR3M / 6.3 jack connection cable, ActiveGard
Sennheiser	HMD 26-II-600-S mit XLR3M / 6,3 Jack plug	Headset, 1 dynamic microphone, supercardioid, with XLR3M / 6.3 jack connection cable, ActiveGard
Sennheiser	HMD 410	headset, condenser microphone, lightweight
Sennheiser		
Sennheiser	HMD 410	headset, condenser microphone, lightweight
Sennheiser	PC3 Headset, 2-ear 2x3.5 jack (available as of October)	High wearing comfort - lightweight, adjustable headband Wired, black 2x 3.5mm jack connector Microphone with noise cancelling
sonoVTS	Adapter Fischer 5p. > XLR 4p.	
SONOVTS	Headset Adapter XLR4/F - 2x Klinke 3,5mm/F	
Telex	PH-88	headset, dynamic microphone
Telex	RTS EMV-2	RTS Earset bestehend aus: RTV-04: Driver 125 Ohm CMT-2: Gerades Kabel mit 1,5mm Klinke AEF-3: Nylon Earloop

Headphones - Accessories

AkG	K 109 S	stereo headphone, suitable in loud environment
AkG	K 140	stereo headphone
AkG	K 500	stereo headphone
Behringer	Powerplay P1, In-Ear Monitor Amplifier	Wired in-ear system with volume control Balance control Mono or stereo mode switchable Output impedance: 10 Ohm Input: 2 XLR sockets Power supply via 9V battery or power supply (both not included) Incl. peak limiter Headphone output: mini jack Metal belt clip Mounting on microphone stand possible to 5/8" or 3/8" thread
Beyer Dynamic	DT 250	stereo headphone
Beyer Dynamic	DT 250	stereo headphone
Beyer Dynamic	DT 770	stereo headphone, 80 Ohm
Beyer Dynamic	Headzone PRO XT	5.1 Monitoring System für Headphones. 1 U 19" Basestation
Fischer Amps	Hardwired In Ear Belt Pack	Headphone-Amp
MB Quart	QP 805	stereo headphone, solid construction
Phonak	Invisity-VHF Intercom Receiver 217 MHz	RF miniature receiver 214,000 MHz - 220,000 MHz
Sennheiser	HD 265	stereo headphone
Sennheiser	IE1	stereo earpiece (for IEM)
Sennheiser	IE4	In-ear Headphone
Sennheiser	HD 405	ear clip

Manufacturer	Item	Description
Shure	E 1	stereo earpiece (for IEM)
Shure	E3	stereo earpiece (for IEM)
Shure	SE535	Are suitable for in-ear monitoring on stage. -Transparent cable and housing -Impedance: 36 Ohm -Sensitivity: 119 dB SPL/mW -Frequency range: 18 - 19,500 Hz
Sonifex	RB-HD61 Headphone Amp	Stereo Headphone Amplifier
Sonifex	RB-HD6 Headphone Amp	6-way headphone amp. for use in distribution-mode or 6x1-mode.
Technics	CD 250 Digital Reference	stereo headphone
Voice-technologies	Audio Implements	earpiece, with elastic tube

Monitors and Displays

	Soundweb BLU-ANA-IN	Analog Audio IN Card
AkG	C 406	clip microphone with 12,5 cm gooseneck
AKG	C 408	clipmicrophone with gooseneck, 2cm, hypercardioid
AkG	C 409	clipmicrophone with gooseneck, 10cm
AkG	C 414 B-ULS	large diaphragm condenser microphone, multiple polar patterns
AkG	C 414 B-XLS	large diaphragm condenser microphone, multiple polar patterns
AkG	C 747	hyper-cardioid microphone, gooseneck, 10cm,
audio-technica	AT 897	shotgun-microphone
audio-technica	AT815b	shotgun-microphone, condenser, 46 cm long
audio-technica	AT835b	shotgun-microphone, condenser, 37 cm length
audio-technica	BP4029	Stereo Shotgun, Phantom-powered (11 bis 52 Volt)
audio-technica	MT830C	Omnidirectional Condenser Lavalier Microphone
audio-technica	MT830R	Omnidirectional Condenser Lavalier Microphone
BON	BSM-183H	18.5" 3G/SD-SDI & HDMI High Brightness Field Monitor features a 1200 cd/m ² daylight-viewable LCD screen. The high brightness preserves contrast and prevents the on-screen image from getting washed out. The 1366 x 768 LED-backlit LCD panel
Bon	BSM-213N3G Monitor	21.5 High Brightness 3G/HD/SD-SDI & HDMI Monitor w/ PIP, Waveform, Vectorscope, Timecode & Audio Meters
BSS	Minidrive FDS 334	crossover, speaker-processor
BSS	Soundweb BLU-160	Soundweb Audio Interface with digital Audio Bus
BSS		Analog Audio IN Card
BSS	Soundweb BLU-DIG-IN	Digital Audio IN Card
BSS	Soundweb BLU-DIG-OUT	Digital OUT Card
BSS	Soundweb SW9088	programmable DSP-matrix (delay, equalizer, dynamics, mix), 8x line in, 8x line out
cedar	DNS-1500	Dialogue Noise Suppressor
Dell	P2213 Monitor	TFT Monitor 22 Zoll
Dell	U2412M Monitor	TFT Monitor 24"
DirectOut Technologies	DirectOut Split Converter	4-Channel MADI Splitter 2x optical SC multi mode, 2 x BNC
Dolby	DP 570 Dolby E Multichannel Audio Tool	Dolby Digital und Dolby E und surround monitorunit and META data editor, analogue und digital I/Os
Dolby	DP 571 Dolby E Encoder	up to 8 channels, various input-formates and word-lengths, 25 und 29,97 video-frames
Dolby	DP 572 Dolby E Decoder	up to 8 channels, various input-formates and word-lengths, 25 und 29,97 video-frames
DPA	4060 miniature-microphone (beige)	condenser lavalier microphone, omnidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA		

Manufacturer	Item	Description
DPA	4060 miniature-microphone (black)	condenser lavalier microphone, omnidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	4060 miniature-microphone (white)	condenser lavalier microphone, omnidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	4061 Lavalier-Mikrofon (black)	condenser lavalier microphone, low sense, onidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	4061 miniature-microphone (white)	condenser lavalier microphone, omnidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	4066 headband-microphone, beige	condenser microphone, omnidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	4066 headband-microphone, black	condenser microphone, omnidirectional, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	4066-OC-A-F03-LH headband-microphone, beige	Is a neckband microphone with omnidirectional polar pattern in medium size. It has a frequency response of 20 to 20,000 Hz and comes with two interchangeable metal grilles that increase the volume by either 3 dB at 8 to 20 kHz, or 10 dB at 12 kHz. The microphone has also been equipped with the powerful CORE amplification technology, resulting in a dynamic range of typ. 111 dB.
DPA	4060 miniature-microphone (black)	condenser lavalier microphone, cardioid, for Sennheiser Series 2000 - 9000 / Wisycom
DPA	DUA 0560 Windscreen	
DPA	MHS6000	microphone holder for strings
Drawmer	DS201 Dual-Gate	2 CH gate 1 U
Drawmer	DS404 Quad-Gate	4 CH Gate 1 U 19"
Dspecialists	ISOSTEM Expert	Upmixer This version contains the full range of functions and all setting options. Various parameters can be defined individually via a GUI and saved as presets. Up to 6 presets can be saved and retrieved as well as transferred to further ISOSTEM devices
DTO	testarticle	
ELo Touchsystems	ET1515L	15" LCD Touch Monitor
Grundig	50 VAE 70	Vision 7 - Fire TV (50 VAE 70) 127 cm (50 Zoll), Fernseher (Ultra HD, Alexa-Sprachsteuerung, HDR)
Hewlett Packard	LE2002x	20" LCD TFT Monitor
Imagine	AES6800+BD	1x9 DA, AES/EBU unbalanced, 2 slots
Imagine	ARG6800+D Distribution amplifier	Analog audio remote Gain, DA balanced (dual 1x4 or singel 1x8) Timecode distribution
Imagine	SELOPT-AAEX1-AABS	Analog audio expansion front module, adds more inputs and outputs to FS/XD/ENC/DEC, includes single back module with two Weidmuller connectors for 8 analog (balanced) inputs and 8
Imagine	X100OPT-ADVAUD	Advanced Audio Submodule
JVC	DLA-SX21	
Klark Teknik	DN 500	4-ch. compressor/limiter
Klark Teknik	DN 7204	delay + EQ
Lake People	F622	2x 1 in 8 Wordclock Distribution
Lake People	Lake People ADC C440	24BIT / 96kHz Analog-Digital Converter
Lake People	MIC-AMP F355	Two-channel ultra-low noise microphone preamplifier with excellent audio performance
Lexicon	960 L	24bit/96khz, 3DPM algorithm, multichannel surround, stereo reverb processing, 8x XLR in/out, 4 AES/EBU I/O, LARC-2 remotecontrol, eight touchsensitiv motorfader
LG	55" UHD Display	

Manufacturer	Item	Description
Lilliput	FA1046-NP/C	10,4" TFT LCD Monitor, Touch screen, HDMI IN, DVI IN
Lilliput		17.3" 1U Rackmounted Drawer Monitor with HDMI / SDI Input
Linear acoustic	AERO.air	5.1 Surround Field Synthesizer / Loudness manager / AC3 - Encoder
Linear acoustic	AERO.qc	5.1 Surround Field Loudness Measurement, Upmix Processing, Loudspeaker-Control
Lynx	C AD 5320 Converter	Dual Analog Audio to AES Converter
lynx	C DA 5220 Dual AES to Analog Audio Converter	
Meyer Sound	LD-2 Stereo Line Driver	parametric EQ
Milab	DC 96 B	condenser microphone
Milab	LSR 2000	condenser microphone, cardioid
Neumann	AK 30	condenser capsule, for KM100-system, omnidirectional
Neumann	AK 40	condenser capsule, for KM100-System, cardioid
Neumann	AK 50	condenser capsule, for KM100-system, hypercardioid
Neumann	BS 945	phantom power unit
Neumann	U 87	large diaphragm condenser microphone, multiple polar patterns
Neumann	KA 100	cable adapter
Neumann	KM 100	DC supply / preamp, incl. AK30/40/50 condenser capsule
Neumann	KMR 82 i	condenser shotgun microphone
Neumann	KMS 84	condensator microphone, cardioid
Neumann	KVF 158	700mm capsule-extension, 700 mm
Neumann	KVF 158	700mm capsule-extension, 700 mm
Neumann	LC3	patchcord, 3,5m
Neumann	LC3 short	
Neumann	MNV 100	auditorium hangar for AK capsules
Neumann	SMK 100	gooseneck with cable, 160mm
Neumann	SMK 100 / 2	double gooseneck
Neumann	TLM 170	large diaphragm condenser microphone, multiple polar patterns
Neumann	U 87	large diaphragm condenser microphone, multiple polar patterns
Neumann	USM 69	large diaphragm condenser microphone, multiple polar patterns
Panasonic	BT-LH1700WE	LCD 17" monitor, SDI, HDSDI, analog video, componente, VGA
Panasonic	TX-24FSW504	LED TV mit internem IP Video Encoder
PHILIPS	49BDL5057P/00	P-Line Full HD-Display. 48,5" Video-In 1 x DisplayPort 1.2 1 x DVI-I 2 x HDMI 1.4 2 x USB 2.0 1 x USB 2.0 Audio In 3,5-mm-Buchse
Philips	Philips 43BDL3010Q	Bildschirmgröße diagonal (cm): 108 cm Bildschirmgröße diagonal (Zoll) :42,5 Zoll Auflösung des Displays : 1.920 x 1.080p Videoformate: 1.080p, 60 Hz 1.080i, 60 Hz 1.080i, 50 Hz 720p, 60 Hz 576p, 50 Hz 576i, 50 Hz 480p, 60 Hz 480i, 60 Hz
Phonak	proVocanto	Headband microphone
Sabine	ADF 1201	mono feedback suppressor
Sabine	ADF 4000	stereo feedback suppressor, digital-graphic EQ, real-time analyzer, limiter, delay
Samsung	UE-32M5075	32" All image content is analyzed with the latest image enhancement algorithms. This ensures high-quality image reproduction with reduced image noise. Enjoy a clearer picture.
Samsung		

Manufacturer	Item	Description
Samsung	UE40ES6300S	
Samsung	UE46ES6300S	
Samsung	UE48H6290SS	
Sanken	CSS-5	stereo condenser shotgun microphone: (48 V+/- 4 V)
Schoeps	BLM 03 C	condenser-capsule, for CMC 6
Schoeps	CMB-1	batterie pack for CMC 6
Schoeps	CMC 5	amplifier / power-supply, incl. clamp
Schoeps	CMC 6	amplifier / power-supply, incl. clamp
Schoeps	CMC MK 2	condenser capsule for CMC 6, omnis
Schoeps	CMC MK 21g	condenser capsule for CMC 6, wide cardioid
Schoeps	CMC MK 3	condenser capsule for CMC 6, omnidirectional
Schoeps	CMC MK 4	condenser capsule for CMC 6, cardioid
Schoeps	CMC MK 41 (S)	condenser capsule for CMC 6, supercardioid
Schoeps	CMC MK 41 S	condenser capsule for CMC 6, supercardioid / highpass
Schoeps	CMC MK 5	condenser capsule for CMC 6, cardioid / omnidirectional
Schoeps	CMC MK 6	condenser capsule for CMC 6, cardioid / omnidirectional / figure-8
Schoeps	CMIT 5U	shotgun-microphone
Schoeps	CMIT 5U DEMO	condenser-capsule, for CMC 6
Schoeps	RC 1200g, active tube for colette	surface finish: matt gray
Schoeps	RC 350g, active tube for colette	surface finish: matt gray
Schoeps	RC 700g, active tube for colette	surface finish: matt gray
Schoeps	VST 62 IUg	phantom-powered stereo amplifier for RCY 1200lg
Sennheiser	BF 5032	condenser microphone
Sennheiser	MKE lavalier-mikrofon	condenser lavalier microphone, exchangeable capsules, for Sennheiser Series 2000 - 9000 / Wisycom
Sennheiser	MKH 60	condenser shotgun microphone
Sennheiser	MKH 70	condenser shotgun microphone
Sennheiser	MSPU4R phantom-power-adapter	XLR - phantom-power-adapter for Lavalier-microphones with 3-pin Lemo Connector
Shure	Beta 87	condenser microphone, super-cardioid
Shure	MX418/S	gooseneck microphone
Sonifex	RB-DA4x5	Distribution/Mixer, 4-Inputs, 4 x 5 Outputs
sonoVTS	HD2line PDI 24W-C	24" HD2line Pro LC Display
sonoVTS		
sonoVTS	HD2line PDI 24W-C	24" HD2line Pro LC Display
sonoVTS	HD2line PDI 24W-C	24" HD2line Pro LC Display
sonoVTS	HD2line PDI 24W-C	24" HD2line Pro LC Display
sonoVTS	HD2line PDP 37W	37" HD2line Pro LC Display
sonoVTS	HD2line PD20W-B	20" Multiformat HDTV/SDTV LCD Monitor, 2x HDS DI input , DVI input, RGB input, CVBS input
sonoVTS	HD2line PD20W-B	20" Multiformat HDTV/SDTV LCD Monitor, 2x HDS DI input , DVI input, RGB input, CVBS input, 1680 x 1050 px native Resolution, Contrast 800:1, 300cd/m² brightness, VESA 100mm Mount
sonoVTS	HD2line PDP 17,3W	17,3" Full HD Monitor, Inputs: DVI-I, VGA, RGB, FBAS. 3G - SDI, 1920 x 1080 Pixel
sonoVTS	HD2line PDP 17W-IPS-B	17" HD2line Pro LC Display
sonoVTS	HD2Line PDP 21,5W-B	21,5" Pro LC Display 3G
sonoVTS	HD2line PDP 24W-B	24" HD2line Pro LC Display
sonoVTS	HD2Line PDP 24W-C2	
sonoVTS	HD2Line PDP 42W	42" HD2line Pro LC Display
sonoVTS	HD2line PDP 42W-B	42" HD2line Pro LC Display
sonoVTS		47" HD2line Pro LC Display
sonoVTS	HD2line PDP 49W	49" HD2line Pro LC Display
sonoVTS	HD2line PDP 55W-B	55" HD2line Pro LC Display
sonoVTS	HD2line PDP 55XSB	almost frameless 55" HD2line Pro LC Display

Manufacturer	Item	Description
sonoVTS		65" HD2line Pro LC Display
sonoVTS	HD2line PD17W-IPS	17" Multiformat HDTV/SDTV LCD Monitor, 2x HDS DI input , DVI input, RGB input, CVBS input, 1280 x 768 px native Resolution, Contrast 600:1, 350cd/m² brightness, VESA 100mm Mount
sonoVTS	HD2line PDP-55XSB-B	55" seamless HD-Display inc.PDP SDI-3G-F Input-Card supplies 525i, 625i, 720p, 1080i, 1080p
sonoVTS	HRDP 170-A	17" 1920*1080 Full HD
sonoVTS	HDQLINE HRDP 240-A	
sonoVTS	HDQLINE HDP 185-A	18,5"
sonoVTS	HDQLINE HDP 215-A	22" , 1920 x 1080, HD Display
sonoVTS	HDQLINE HDP 240-A	24"High Performance WUXGA Display (1920x1200)
sonoVTS	HDQLINE HDP 490-A	49"
sonoVTS	HDQLINE QDP 173-A	17,3", 3840 x 2160, UHD Display
sonoVTS	HDQLINE QDP 240-A	24", 3840 x 2160, UHD Display
sonoVTS	HDQLINE QDP 320-A	32", 3840 x 2160, 4K Display
sonoVTS	HDQLINE QDP 490-A	49", 3840 x 2160, 4K Display
sonoVTS	HDQLINE QDP 490-B	49", 3840 x 2160, 4K Display
sonoVTS	HDQLINE QDP 550-A	
sonoVTS	HDQLINE QDP 650-A	65", 3840 x 2160, UHD Display
sonoVTS	HDQLINE QRDP 310-A	31", 4096 x 2160, 4K Display
sonoVTS	HDQLINE TFT17QR	17"TFT, 3G LCD Display mit Audio Output 3,5 Klinke
SONOVTS	Monitor Wall L-shaped	24x HD2line 55 "PDP 55XSB-B Monitor 24x alu wall segments 8x alu socket
sonoVTS	TFT17HD	17" TFT HD Display-W, 1920 x 1080 ,12V DC (ext.power-supply) 2x SDI/HD IN, 1x DVI IN, 1x VGA IN
sonoVTS	TFT17QT	17" TFT HD Display-W
sonoVTS	TFT22Q	
sonoVTS	TFT22QB	22 inch widescreen display, 2x 3G HD-SDI, 1x DVI-D, 1x DisplayPort
sonoVTS	TFT24W	
sonoVTS	TFT32Q	
sonoVTS	TFT42QB	42 inch widescreen display, 2x 3G HD-SDI, 1x DVI-D, 1x DisplayPort, SFP-Slot (optional)
sonoVTS	TFT47Q	
sonoVTS	VTS-TFT47	
Sony	BKM-16R	Monitor Contrl Unit for BVM-L and PVM-L series
Sony	BKM-FW16	HD-SDI/SD-SDI-Board, 1x IN, 1x OUT Embedded Audio Support
Sony	BVM-A14F5M	
Sony	BVM-F170	16,5" (1920 x 1080 Pixel) OLED Monitor
Sony	BVM-F250	24,5" (1920x1080) OLED Monitor
Sony	BVM-L170	17" Multiformat-Widescreen-LCD-Referencemonitor, Full HD (1920 x 1080 Pixel)
Sony	Sony FWD-S47 H1	LCD 47" monitor, SDI, HDS DI,DVI
Sony	LMD 2451W	Multi-Format Widescreen Video Display 24", incl. HD-SDI Option
Sony	LMD-941W Monitor	portable full HD Display . Two 3G/HDS DI inputs / HDMI
Sony		
Sony	PVM-A170	OLED Monitor
Sony	PVM-A250	OLED Trimaster Monitor 25"
SPL	Model 2489	Surround Monitor Controller
t.c. electronic	D22	stereo broadcast delay, analog/digital
t.c. electronic	DB6 AES 16	Broadcast Transmission Loudness Processor, balanced AES In - Outs, Loudness Wizzard App, Radar - Meter, Surround Up - / Downmix
t.c. electronic	DBMAX	multiband-stereo compressor/limiter (limiter for TX-lines)
t.c. electronic	LM2	Stereo Loudness Meter / Limiter for Ingest. Radar Display via TC Icon Software or DAW Plug-In. In-/ Out via analog/ AES / ADAT/ Toslink

Manufacturer	Item	Description
Tram	TR 50	condenser lavalier microphone, omnidirectional, incl. phantom-power-adapter
Tram	TR 50 Clip-on microphone	condenser lavalier microphone, omnidirectional, for transmitters or phantom-power-adapter
TVlogic	LVM 243W	24" (61cm) Multiformat LCD Monitor, 3G / Dual Link, HDMI, DVI-I, YUV, Y/C, FBAS
TVlogic	LVM-242W	24" HD Multi-Format-LCD-Monitor
TVlogic	LVM-323W	Multi Format LCD Monitor
TVlogic	VFM-056W	5,6 Zoll LCD Viewfinder, HD/SD-SDI, Composite, Y/C, YUV, HDMI
Waves	MaxxBCL Hardware Processor	Digital high-end Dynamik- und Low-Frequenz Processor
WAVES LIVE	WSG Y16V2	Mini-YGDAI Sound Grid I/O card for Yamaha
Wohler	RM-2443W-HD	4-Display HD-SDI Monitoring, 2 HE
Yamaha	DME 64 digital mixing engine	programable DSP-matrix (delay, equalizer, dynamics, mix, etc). up to 64 ins and outs by using digital IO-cards. with analog cards 32x32. variable slot-assembling
Yamaha	Q2031B Graphic Equalizer	31-band grafik analog stereo equalizer
Yamaha	SPX 2000	effects-prozessor
Video - Interfaces		
AJA	HDP2	HD-SDI -> DVI Converter
Amazon Basics	Audio Extractor Converter, HDMI to HDMI + Audio (SPDIF+RCA Stereo)	<ul style="list-style-type: none"> - HDMI to HDMI Audio Extractor Converter - Supports HDMI source devices without dedicated audio output - Supports two-channel left-right or SPDIF stereo output, as well as uncompressed and compressed audio - Supports up to 4k video resolution; 8-bit 4K (30Hz), 12-bit 1080p (60Hz) or 12-bit 720p/1080i (60Hz) plus 3D formats - Compatible with devices such as Blu-ray, DVD/HD/DVR players, Cable/Satellite, Amazon Fire TV, Apple TV, PS3/4, Xbox, PC/Laptop, HD Cameras and more
Antrica	ANT -2601	H.264 / H.265 Decoder
Antrica	ANT -2601	H.264 / H.265 4 Channel Encoder
Beyer Dynamic	M58	reporter-microphone, omnidirectional
Beyer Dynamic	SHM 424	dynamic microphone
Blackmagicdesign		Signal converter for monitoring in full resolution HDTV with DVI, DisplayPort and HDMI monitors
Blackmagicdesign	Micro Converter SDI to HDMI (available as of October)	4: 4: 4 SDI video, lookup tables via USB and analog audio outputs. Converter SDI to HDMI, no external power supply, DC over USB connector .
Blackmagicdesign	Mini Converter HD/SD-SDI/Analog	HD/SD-SDI/Analog Converter Deembedder (Analog/AES)
Blackmagicdesign	Mini Converter, Analog to SDI	Analog HD/SD Komponente, NTSC, PAL oder S-Video zu SDI out mit balanced AES/EBU und Analog Audio embedding
Blackmagicdesign	Mini Converter, HDMI to SDI 4K	HDMI- to SDI-, HD-, 3G. Audio Embedder to SDI
Blackmagicdesign	Mini Converter, SDI to Analog	
Blackmagicdesign	Mini Converter, UpDownCross	Up,Down and Cross Conversion NTSC/PAL Standard Conversion 3G-SDI Distribution Amplifier
Digitus	DS-42211 DVI Splitter	With a DVI video/audio splitter it is possible to display a signal from a DVI video source on several monitors/speakers. <ul style="list-style-type: none"> - DVI video/audio splitter, 4-port - Supports max. resolution up to 1920x1200 pixels and Full HD 1080p - Automatic power-save when Video input is lost - Crisp clear video images - LED indicators for signal activity monitoring - Support EDID. HDCP and is Blu-ray ready
Electro-Voice	RE 27 Microphone	dynamic microphone dynamic large-diaphragm microphone (cardioid) switchable high-pass filter - 2 stages HF cut

Manufacturer	Item	Description
Grass Valley	DSK-3901	DSK-3901 is a low cost, modular downstream keyer, with two independent pairs of fill and key inputs. This 3G/HD/SD keyer is ideal for inserting two external character generator feeds over program video. Up to 10 channels of keying can be housed in a single 3 RU Densité 3 frame. An integrated audio mixer provides eight channel voiceovers, as well as audio clip storage and playout. Background audio is automatically ducked during voiceovers. Audio can be accepted as embedded audio or as four external AES inputs. The audio mixer features separate processing for the program and the preview chains.
Imagine	Imagine ENC6801+D	The ENC6801+D encoder is a high-precision, 12-bit digital encoder that supports NTSC, PAL-B and PAL-M standards.
Imagine	SEL-1J2KD1-EOS Decoder	One Channel JPEG2000 Decoder
Imagine	SEL-1J2KE1-EOS Encoder	1-Channel JPEG2000 Encoder
Imagine	SEL-1UHD3-FS-S	Single channel Quad Link UHD-1 frame sync with embedded audio processing, includes front and single back module with four HD-BNC input connectors, four HD-BNC output connectors, GPI and serial data port
Imagine	SEL-2J2KD1-EOS JPEG2000 compression decoder	JPEG2000 compression decoder, includes 2x HD/SD channels or 1x 3G channel J2K decoding, a single back module with 8x HD-BNC connectors for SDI/ASI signals and dual SFP electrical/optical support for 1GbE transport over IP (order SFP options separately).
Imagine	SEL-2J2KE1-EOS JPEG2000 compression encoder	JPEG2000 compression encoder, includes 2x HD/SD channels or 1x 3G channel J2K encoding, a single back module with 8x HD-BNC connectors for SDI/ASI signals and dual SFP electrical/optical support for 1GbE transport over IP (order SFP options separately).
Imagine	SEL-4CQS1-S	4x4 or Dual 2x2 CQS Clean and Quiet SDI Switcher, line sync or frame sync mode, includes single back module with 2 HD-BNC input connectors, 2 inputs on SFP (SFP+2ERX+NR+L dual HD-BNC input SFP included) and 4 HD-BNC outputs, GPI and serial data port
Imagine	SELOPT-DAEX1-AESCS	Unbalanced AES audio expansion front module, adds more inputs and outputs to FS/XD, includes single back module with HD-BNC connectors for 8 AES (unbalanced) inputs and 16 AES (unbalanced) outputs
Imagine	SFP 6800+D-SIMPLE	Simple, flexible processing module comes with 6 SFP cages that can be populated with various types of SFPs in any order or configuration. Examples of SFP types are Fiber, HD-BNC or HDMI.
Imagine	XOS+2+OP+C2729S	Dual SD fiber transmitter, 1270 nm and 1290 nm CWDM
Imagine	XOS+2+OP+C3133S	Dual HD/SD SDI Fiber Transmitter, 1310 nm and 1330 nm CWDM
Imagine	XOS+OP+C31S	HD/SD SDI single channel Fiber Transmitter, CWDM compatibel, 1310nm
Imagine	XOS+OP+C33S	HD/SD SDI single channel Fiber Transmitter, CWDM compatibel, 1330nm
Lynx	C DA 3000 8 bit SDI to Analog Video Converter	SDI-SD to Analog Converter
Lynx	D VD 3620 Video Distribution Amp	Dual HD/SD-SDI Distribution 2x 1/4 or 1x 1/8
Matrox	Convert DVI	HD-SDI Scan Converter with Genlock
Network	FM-AV-HD-XMUX-13T	HD/SDI Embedder/Deembedder. 4 x AES in/out. Additional Upstream Fiber-out on single mode 9/125 simplex SC.
Network	FM-AV-HD-XMUX-R	HD/SDI Embedder/Deembedder. 4 x AES in/out. Additional Downstream Fiber-input on single mode 9/125 simplex SC.
Neumann		
PureLink	OLC/OLCX	DVI <-> Fiber Adapter 4x LC Multimode
Sennheiser	BF 541	dynamic microphone
Sennheiser	MD 421	dynamic microphone

Manufacturer	Item	Description
Sennheiser	MD 46 Microphone	Dynamic reporter microphone special interview and reportage microphone dynamic cardioid characteristic with long handle length Dimensions (L x Ø): 250 x 49 mm Characteristic: Cardioid Frequency range: 40-18,000 Hz Sensitivity (free field, no load) 1 kHz 2.0 mV/Pa+-2.5 dB Nominal impedance at 1 kHz 350 Ohm min. terminating impedance 1000 Ohm
Sennheiser	SKM 5000	766,125-789,300 Hz
Sennheiser	SKM 5200N Microphone 790 - 826 MHz CH 61/63	handheld transmitter, Neumann KK 105 capsule
Sennheiser	SKM 9000 630-718 MHz (B1-B4)	Digital Wireless Handheld Mikrophone Freq. range 630-718 MHz, Color: Capsule KK204 ni .
Sennheiser	SKM 9000 COM 710-798 MHz (B5 - B8)	Digital Wireless Handheld Mikrophone, incl. Command option, Capsule KK204 ni .
Shure	Beta 52	bass microphone
Shure	Beta 56	dynamic microphone
Shure	Beta 57 MR	dynamic microphone
Shure	Beta 58	dynamic microphone
Shure		
Shure	SM 57-LC	dynamic microphone
Wisycom	MTH300 560 - 660 MHz	handheld transmitter
Wisycom	MTH300 microphone B4 630 - 750 MHz	UHF handheld transmitter with Schoeps capsule MCM301, 50mW, 630-750 MHz, display, switching bandwidth 12 TV channels, power supply 2xAA (Mignon)
Wisycom	MTH300 microphone B5 700 - 822 MHz	UHF handheld transmitter with Schoeps capsule MCM301, 50mW, 700 - 822 MHz, display, switching bandwidth 12 TV channels, power supply 2xAA (Mignon)

Signal Processing Video

	Selenio	Selenio 3RU Frame, two AC PSU, two external reference looping BNC inputs, two controllers (each one RJ45 for control)
360 Systems	360 Systems, Instant Replay 2	Jingle Audio Player
AJA	AJA HD/SD Distribution AMP	1x4 mini - HD-SDI/SDI-Distribution/Repeater
AJA	GEN 10	SD/HD/AES sync generator. 7 outputs including 2 groups of independently controlled SD/HD sync outputs and 1 AES-11 output. The SD outputs can be switched between Color Black or Color Bars. HD tri-level sync can be switched between 19 different HD formats including all that are in use today. The AES-11 output can be switched between SILENCE and TONE.
AJA	HA5	
AJA	HA5-4K	HDMI to 4K/UHD SDI
AJA	Hi5 4K Plus Mini-converter	Mini-converter 4K/HD-SDI to HDMI. AJA's Hi5-4K-Plus preserves your vision with pristine image fidelity and HFR support up to 60p for 4K/UltraHD SDI to HDMI 2.0 conversion needs. The Hi5-4K-Plus can also generate HDR metadata in accordance with HDMI v2.0a/CTA-861.3 and includes HLG support. Hi5-4K-Plus provides a simple monitoring connection from professional 4K devices using Quad 3G-SDI, Quad 1.5G-SDI, or Dual 6G-SDI to HDMI 2.0a/CTA-861.3 and includes HLG support.
AJA	Hi5-4K	4 x SDI to HDMI (4K) converter. Two Sample Interleave (2SI) or Square Division (Quadrant) source mapping
AJA	HA5	
Avago	SFP Avago AFBR-703SDZ-NA1 850 nm 10 Gbit/s	Avago AFBR-703SDZ-NA1 850 nm 10 Gbit/s Transceiver SFP+ SR 332-00279R6+A0
Datapath	FX4/H Display Wall Controller	Stand-Alone Display-Wall-Controller
Decimator Design	MD-Cross Converter	MINIATURE (3G/HD/SD)-SDI / HDMI CROSS CONVERTER with Scaling and Frame Rate Conversion
Denon	DN C-680	CD-player, AES/EBU, SPDIF , 19", 3U

Manufacturer	Item	Description
Denon	DN M1050 R	MD-recorder, AES/EBU, SPDIF , incl. hot-start-board, 19", 3U
Denon	DN-501C	CD-player, AES/EBU, SPDIF , 19", 1U, USB Port
Diverse	Harddisk Drive	500GB USB, Firewire, eSATA
emSFP by embrionix	SFP EB60LC2R-MN 1150-1600	
FINISAR	SFP HUBS-SFPC1110	1000BASE-T Copper SFP Transceiver FCLF-8521-3
Genum	SFP GO2927-CM 1270-1610nm	The video SFP GO2927-CM is a medium reach optic video SFP . This SFP is specifically designed to support pathological test patterns. This SFP is designed to receive two SDI signals (3G/HD/SD-SDI/ASI) over single mode fiber (9um/125um) via LC connectors. The optical receivers inside are SMPTE compliant video.
Genum	SFP GO2928-3131CM 1310nm	The video SFP GO2928-3131CM is a medium reach optic video SFP . This SFP is specifically designed to support pathological test patterns. This SFP is designed to transmit two SDI signals (3G/HD/SD-SDI/ASI) over single mode fiber (9um/125um) via LC connectors. The laser drivers inside are SMPTE compliant video.
Genum	SFP OH RX 1 1270-1610nm	Single Optical Receiver (RX) SFP Module (1270-1610nm) LC connectors
Grass Valley	Densité 3 mini (DSK-3901)	3G/HD/SD Downstream Keyer
Imagine	6800 ETH	Ethernet resource card for FR68** Frames
Imagine	ACO6800+DSD Basic Dual Switchover for SD/HD/ASI Sources	Intelligent Dual Switchover for SD/HD/ASI
Imagine	DA-DHR6802+D Distribution Amplifiers	Dual 1x4 or single 1x8 distribution amplifier, 3G/HD/SD/ASI
Imagine	DA-DHR6804+D Dual Reclocking 3G/HD/SD/SDI	Low Power Dual 1x4 DA or single 1x8 with secondary back-up input and built-in ACO, 3G/HD/SD/ASI with reclocking, 2 slots
Imagine	DA-DHROOE 6803+	Dual-Channel 1x4 or Single-Channel 1x8 with Built-In ACO, Optical Distribution, O-to-E, 3 Gb/s, HD, SD, ASI, Reclocking
Imagine	DA-HR6802+ Video distribution amplifier	HD/SD Video Single 1x8.
Imagine	DAC 6800+BCA4D	converter two AES inputs to four analog audio outputs
Imagine	DEC6800+D Decoder Analog Digital Wandler	The DEC6800+D is a compact, high-precision, 12-bit decoder that converts NTSC and PAL analog composite signals into superior-quality component (4:2:2) digital video.
Imagine	FR6822+QXFE+6822+AC FRAME	6800er Platform, Mainframe, 2 power-supplies, Ethernet, HTTP, FANS, ONE PS, QSEE Frame, 2RU, Ethernet resource including HTTP protocol for communication, no back, all blanks with fan (incl. one 6822+AC power supply) support QSEecompliant
Imagine	HDC6800+A Downkonverter	HDTV Utility Downconverter, Q-SEE™-Compliant
Imagine	HDX6800+BC8D Auto-sensing HD/SD Multiplexer	Auto-Sensing HD/SD-SDI Demultiplexer with 8 AES Outputs
Imagine	HFS6801+D	Auto-Sensing HD/SD-SDI Video Frame Synchronizer/Processor
Imagine	HMX6800+BC8D	Auto-Sensing HD/SD-SDI Multiplexer with 8 AES Inputs
Imagine	HMX6803+	Auto-Sensing HD/SD Audio Embedder with up to 8 AES Inputs
Imagine	ICE 6800+D	Interface Card to Ethernet module
Imagine	OP+AVR+D Optical Receiver	1 video analog, 4 audio analog , PIN receiver
Imagine	OP+AVT+2+13D Optical Audio Receiver	2 video, 8 audio, 1310 nm FP laser
Imagine	OP+AVT+C35D Audio Channel Optical Transmitter	1 Analog Video, 4 Analog Audio Fiber Transmitter, 1350nm
Imagine	OP+AVT+C37D Audio Channel Optical Transmitter	1 Analog Video, 4 Analog Audio Fiber Transmitter, 1370nm
Imagine	OP+ETH+C43D Wideband Tranceiver	10/100/1000Base-T Ethernet, CWDM DFB laser, wideband tranceiver, 1430 nm, 10 Mb/s, 100 Mb/s and 1000 Mb/s
Imagine	OP+ETH+C45D Wideband Tranceiver	10/100/1000Base-T Ethernet, CWDM DFB laser, wideband tranceiver, 1450 nm, 10 Mb/s, 100 Mb/s and 1000 Mb/s
Imagine	OP+SFP+20TX+13+NR	Fiber SFP (1310nm) DUALOPTICAL TX SFP

Manufacturer	Item	Description
Imagine	OP+SFP+2ORX+NR	SFP SERIES: DUAL OPTICAL PIN-RX (NON RECLOCKING)
Imagine	OP+SFP+20TX+13+NR	DUALOPTICAL 1310NM TX (NON Relocking)
Imagine	OP+SFP+TT+13+13	Fiber SFP (1310nm DUALOPTICAL TX SFP
Imagine	OP+SFP+TT+27+29	
Imagine	OP+SFP+TT+31+33	
Imagine	OP+SFP+TT+35+37	
Imagine	OP+SFP+TT+43+45	
Imagine	OP+SFP+TT+47+49	
Imagine	OP+SFP+TT+51+53	
Imagine	OP+SFP+TT+55+57	
Imagine	OP+SFP+TT+59+61	
Imagine	OXS+2+OP+S Fiber Output Converter Module	OXS-OP+S Dual Channel HD/SDI to Fiber Output Converter Module
Imagine	OXS+OP+S Fiber Receiver	Single HD / SD fiber receiver,
Imagine	SEL-1FS1-EES SINGEL	Single channel frame synchronizer front module with logo generator / inserter, and full embedded audio processing, includes single back module with HD-BNC connectors for SDI and composite input, SDI outputs, 8 AES (unbalanced) input / output ports and socket / plug for 4 GPI inputs, 4 GPI outputs and two serial data connections
Imagine	SEL-2XD1-EES Dual-Channel Video Coversion	Dual-Channel Video Coversion with Advanced Audio Processing Capability. Universal converter
Imagine	SEL-2XD1-EOS	3G HD> HD/SD down converter, high quality +E/O Conversion
Imagine	SEL-DDA1-EES	Dual Distribution Amplifier (SDI/ASI) and Dual Digital (SDI 270 Mb/s) to Analog (NTSC, PAL) module with routing capability, includes back module with HD-BNC inputs and output
Imagine	SEL-FR3-AC-RO-IP-R	Selenio Mainframe, (redundant) power supplies, genlock input boards and Ethernet boards. capacity for 14processing modules.
Imagine	SELOPT-VEX1-EES , VIDEO EXPANSION MODULE	Video expansion module, expansion to FS/XD with single/dual composite analog NTSC/PAL output, includes back module, HD-BNC inputs and outputs
Imagine	SELOPT-VEX1-REL Video Expansion Module	Video expansion module with dual input to output relays, expansion to FS/XD front module, single/dual composite analog NTSC/PAL output, includes back module with dual relays, HD-BNC inputs and outputs single back module
Imagine	SFP+2ERX	DUAL-CHANNEL HD-BNC INPUTS OF SD/HD/3G
Imagine	SFP+2ERX+NR+L	DUAL-CHANNEL HD-BNC INPUTS OF SD/HD/3G (NON Relocking)
Imagine	SFP+2ETX	SFP6800+D*SFP SERIES* Dual HD BNC /TX
Imagine	SFP+2ETX+NR	SFP6800+D*SFP SERIES* Dual HD BNC /TX
Imagine	SFP+TRJ45+1G	Fiber Optic Transceiver Module Ethernet 1.25Gbd 3.3V RJ45 Pluggable, SFP
Imagine	SFS6803+	HD/SD-SDI A/V frame synch and processing amplifier Audio embedder and de-embedder Fiber TX or RX
Imagine	VCA6800+D	analog video, 1x8 DA.
Imagine	VDA6800+	1/8 Analog Video - Distribution
Imagine	X50 Intelligent Frame Synchronizer and Converter	Frame-Synchronizer, Up-/Down-Converter, Color Corrector, Aspect ratio Converter, Embedder/De-Embedder, Audio-Shuffler
Imagine	X85	Frame-Synchronizer, Up-/Down-/Cross-Converter, Format-Converter, Aspect Ratio Converter, Video Delay, Embedder/De-Embedder, Audio-Shuffler, Dolby Processing
Lawo	SFP Mod LC, MM1310nm, MADI	SFP Module MADI 1310nm MM LC Dual Fibre (981/60-80) - to connect multi-mode fibre to a MADI port.
Lawo	SFP Mod LC, SM1310nm, 10GE	for LAN 986/72-10
Lawo	V_pro 8	8 Channel Videoprocessing, Audio Embedder-/ de-embedder via MADI

Manufacturer	Item	Description
Lawo	V_Remote 4 Video-over-IP Encoding and Decoding	Multiple Video-over-IP Encoding and Decoding Platform
Lynx	C AD 5110	Analog Video to SDI Converter
Lynx	C DA 3010 SD converter	10 BIT SDI to Analog Video Converter
Lynx	C DA 5011 SDI to Analog Video Converter	SDI to Analog Conv. & Line Synch
Lynx	D AA 5320 Dual Analog Audio Distribution Amplifier	Dist Amp 1>8 Dual Analog Audio Distribution Amplifier
Lynx	D VA 5710 SD/HD Analog Video Distribution Amplifier	Analog Dis 1/8
Lynx	D VA 5718 Analog Video / Sync Distribution Amplifier	Analog Dis 1/8
Lynx	D VA 5720 SD/HD Dual Analog Video Distribution Amp.	Blackburst Distribution Amp 1>16 Analog Video / Sync Distribution Amplifier
Lynx	D VA 5724 Video / Sync Distribution Amplifier	Dual 1>4 Analog Video / Sync Distribution Amplifier
Lynx	D VA 5760 Analog Video / Sync Distribution Amplifier	1>16 Analog Video Dist Amp
Lynx	D VA 5620 Dual HD / SD SDI Distribution Amplifier	Dual distribution amplifier for SD / HD video
Lynx	D VD 5810 Distribution Amplifier	3Gbit 1>8 SDI/ASI Distribution Amplifier, reclocking
Lynx	D VD 5820 Dual Channel SDI/ASI Distribution Amplifier	3G-HD-SD SDI Dual 1>4 - Single 1>8 Distribution
Lynx	O RX 5800 Fiber Optic to SDI Receiver	Quad Fiber Optic SM to SDI 3 Gbit/s Receiver
Lynx	O TX 5840 SDI/3G to Fiber Optic Transmitter	Quad SDI to Fiber Optic Transmitter SM
Lynx	OH BD 1 1310 Y	Single Optical Transceiver (TX/RX) SFP Module 10Km 1310nm LC connectors
Lynx	OH BD 1 150 Y	Single Optical Transceiver (TX/RX) SFP Module 10Km 1550nm LC connectors
Lynx	P DM 5240 3G/HD/SD 8 Channel Embedder / De-embedder	4x AES Audio Mux/DeMux 3G/HD/SD 8 Channel Embedder / De embedder
Lynx	P DM 5288 SD / HD Multi-format AES Audio Embedder / Deembedder	8x AES Audio Mux/Demux
Lynx	P DX 3264 AES de-embedder	multi-format SD/HD operation with auto detection, de-embeds all audio (8xAES) into 16 x 8 mono output crossbar, 4 x balanced AES3 outputs + unbalanced AES3id outputs provided, audio outputs isolated (transformer coupled), 4 x reclocked SDI outputs function as a 1 > 4 SDI distribution amplifier, remote control via USB service adapter or LYNX control system
Lynx	P DX 3362 analog de-embedder	multi-format SD/HD operation with auto detection, de-embeds all audio (8xAES) into 8 x 4 AES output crossbar, 2 x analog stereo pair outputs, 2 x balanced AES 3 outputs + unbalanced AES3id, analog full scale preset selection 12/15/18/20/22/24 dBu, individual (mono) adjustments for L and R analog gain, selectable left and right channel swap, selectable mute for each stereo pair, selectable de-emphasis for each stereo pair, remote control via USB Service adapter or LYNX control system
Lynx	P MX 3264 AES embedder	AES embedder, multi-format SD/HD operation with auto detection, 4 x AES inputs balanced or unbalanced, selectable sample rate converters on each input, 8 x 16 mono crossbar to configure embedder inputs, existing embedded audio can be replaced, deleted or passed transparently, 4 x SDI outputs with embedded audio, also functions as a 1>4 re-clocking video distribution amplifier, remote control via USB service adapter or LYNX control system
Lynx	P MX 3362 analog embedder	analog embedder, multi-format SD/HD operation with auto detection, 2 x analog stereo pair inputs, analog full scale preset selection 12/15/18/20/22/24 dBu, 4 x 16 mono crossbar to configure embedder inputs, existing embedded audio can be replaced, deleted or passed transparently, 4 x SDI outputs with embedded audio, also functions as a 1>4 reclocking video distribution amplifier, remote control via USB service adapter or LYNX control system

Manufacturer	Item	Description
Lynx	P TG 5610 Video and Audio Test Generator	
Lynx	P VD 5840 FLEXCARD Dual Channel Frame Sync + Audio and Image Processing	Dual 3G/HD/SD Frame Sync incl. 2 Channel License
Lynx	R CT 5010	controller Karte
Lynx	R CT 5023G Rack Controller	Monitor and control all modules installed in a Series 5000 chassis
Lynx	R FR 5012 Mainframe	Mainframe, redundante Netzteile, Ethernet-Web-Interface zur Configuration
Lynx	Yellobrik OBD 1510 D	RS232/422/485 Serial and GPI Bidirectional Fiber Transceiver
lynx	Yellobrik C HD 1802 HDMI to SDI Converter	HDMI to SDI Converter
Lynx	Yellobrik CDH 1811 3Gbit SDI / HDMI / LWL Converter	Fiber in-/out, BNC in-/out, 2 channel analogue and digital audio de-embedding, Output also on HDMI and Fiber singlemode, LC-Connector
Lynx	Yellobrik CDH 1813 Video Converter 3G/HD/SD SDI to HDMI 1.4b	Fiber in-/out, BNC in-/out, 2 channel analogue and digital audio de-embedding, Output also on HDMI and Fiber singlemode, LC-Connector
Lynx	Yellobrik CHD 1812 HDMI to SDI Converter with Frame Synchronizer	HDMI to SDI Converter, Frame Sync, external audio embedding
Lynx	Yellobrik C QS 1441	Bi-directional Single-Link to Quad-Link converter
Lynx	Yellobrik D VD 1817 SDI Distribution Amplifier	3Gbit 1>7 Reclocking SDI Distribution Amplifier
Lynx	Yellobrik DVA 1704 Wide Band 1>4 Analog Video/Sync Distribution Amplifier	Analog Video/Sync Dist Amp 1/4
Lynx	Yellobrik DVD 1806 HD-SDI Reclocking Distribution	3Gbit Recklocking SDI Dist Amp
Lynx	Yellobrik OBD 1810 RX/TX 3Gbit Bidirectional SDI/Fiber Transceiver- 10km	3Gbit HD SDI/Fiber Optic Bidirectional Tansceiver
Lynx	Yellobrik OH-RX-12G-LCe	12Gbit SDI Single Optical Receiver, SDI multi-rate fiber optic receiver for 12G-SDI, 6G-SDI, 3G-SDI and HD-SD Supports 1260 to 1620nm wavelengths
Lynx	Yellobrik OH-TX-12G-LCe	12Gbit SDI Optical Transmitter, SDI multi-rate optical transmitter for 12G-SDI, 6G-SDI, 3G-SDI and HD-SDI 1310nm wavelength (non CWDM). Distances up to 10km** (singlemode)
Lynx	ORR 1802 Fiber SDI Receiver	Dual SDI to Fiber Optic Receiver
Lynx	Yellobrik O RX 1702 Analog Sync / Video Fiber Optic Receiver	Analog Sync / Video Fiber Optic Receiver
Lynx	Yellowbrik ORX 1800 Fiber to SDI Receiver	Fiber to SDI Converter
Lynx	OTT 1812 SDI Fiber Transmitter	Dual 3Gbit SDI to Fiber Optic Transmitter - 10km
Lynx	Yellobrik O TX 1712 Fiber Optic Transmitter	Analog Sync / Video Fiber Optic Transmitter
Lynx	Yellobrik OTX 1742 Analog Sync / Video Fiber Optic Transmitter (CWDM)	
Lynx	Yellobrik PDM 1383 Analog Audio Embedder / De-embedder	Video HD/SD (SDI) In. Analog Audio Embedder/De-Embedder
Lynx	R FR 1000 Rack Frame	Yellobrik 1RU Rack Frame
Lynx	OH RX 1 Y	Single Optical Receiver (RX) SFP Module (1270-1610nm) LC connectors
Lynx	Yellobrik SFP OH TR 1 1310nm	Dual, single Optical Transceiver (TX/RX) SFP Module 10Km 1310nm LC connectors dual
Lynx	Yellobrik SFP OH TR 12G LC	12G SDI Optical Transceiver TX:1310nm - RX:1260nm to 1620nm
Lynx	Yellobrik SFP OH TR 4 1290nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1290nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1310nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1310nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1330nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1330nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1370nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1370nm LC connectors dual

Manufacturer	Item	Description
Lynx	Yellobrik SFP OH TR 4 1390nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1390nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1410nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1410nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1430nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1430nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1450nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1450nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1470nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1470nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1490nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1490nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1510nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1510nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1530nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1530nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1550nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1550nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1570nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1570nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1590nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1590nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1610nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1610nm LC connectors dual
Lynx	Yellobrik SFP OH TR 4 1350nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1350nm LC connectors dual
Lynx	Yellobrik SFP OH-RR-1-LC	
Lynx	Yellobrik SFP OH-TT-1-Y-LC	
Lynx	Yellobrik SPG 1707 HD / SD Sync Pulse Generator with Genlock	Sync Pulse and Tri-Level Sync Generator
Microsens	LWL Konverter MM-SM	
Newtec LiveXpert	Live CG Broadcast HD/SDI Character Generator	Character Generator. Supports TGA,BMP,PNG,TIF,JPG,GIF und Flash animationen (.swf)
Riedel	MediorNet SDI2HDMI	Converts 3G-/HD-/SD-SDI to HDMI, USB powered
SKYLANE	SFP Mod LC, 1310nm, MM, DDM	SFP13002EGxx is a high performance transceiver module for STM1/OC-3 data links over a multimode fiber pair. The maximum reach is 2km, for a 11dB End Of Life (EOL) power budget.
SMART View	DVR-101	DVI Repeater
Snell	ALCHEMIST PH.C-HD Format-changer	1080P 3Gb/s, HD/SD Video Format-changer incl. Timecode Option, Dolby E Option
Sony	MDS-E12	MD-recorder, analog in/out XLR, SPDIF , cable-remote or PC-keyboard, 19", 1U,
Sony	PCM 7050	timecode-DAT recorder, Sony 9-pin, 19", 3U
Sony	PCM R500	DAT recorder, AES/EBU, SPDIF, 19", 3U
Speaka Professional	HDMI Splitter 1x4	
StarTech.com	SFP HUBS-SFPC1110	Cisco SFP-GE-T Compatible SFP Module - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 10/100/1000 Mbps - RJ-45 100m - Cisco IE3400, IE3300, IE3200
Tascam	CD-01U Pro	professionell CD Player
Tascam	CD-RW2000	CD-recorder
Tascam	DA 60 MkII	time code DAT recorder
Tascam	DV-RA1000HD	High-Resolution Recorder with 60GB Hard Drive
Tascam	HD-P2	portable, high resolution stereorecorder . storage-medium CF-card 512MB up to 8GB. recording time for instance on 2 GB card with 48KHz 2 ours stereo oder 4 ours mono. broadcast wave format incl. timecode
tvONE	1T-VS-647	SDI to HDMI Scaler with Audio converts a variety of SDI transmission rates and video resolutions into an HDMI signal.
Western Digital	My Book Studio Edition Harddisk	USB / Firewire / eSATA - Harddisk, 500GB

Manufacturer	Item	Description
Audio - Interfaces		
ANT	telcom C4	compander system for reel-tape-machines
Beachtec	DXA-4	XLR-Adaptor Handycams
Beachtec	DXA-4	XLR-Adaptor Handycams
DirectOut Technologies	Andiamo 2.XT SRC	Converter analog Audio & AES <-> MADI Cascade two ANDIAMO 2.XT SRCs for conversion of 64 channel MADI ports (I/O): 1 x SC-Socket multi-mode & 1 x coaxial BNC, 75 Ω. AES3 ports (I/O): 4 x DSUB-25 (16 x AES3) Analog (I/O): 8 x DSUB-25, balanced, AES59 compliant Word clock (I): 1 x coaxial BNC (75 Ω termination switchable), AES11 (DARS also supported) Word clock (O): 1 x coaxial BNC
Focusrite	Saffire PRO 26	Firewire Audio Interface
Hifonics	DC 5.1 Decoder	AC3 Decoder / 6 analogue RCA outputs
img Stage line	MPS-I	Mic Splitter 1/2
Knacker Elektronik	RS - 110	GSM Interface for i-Phone/Blackberry, other Brand on request
Komplete	Audio 6	
Lake People	DFC C430	AES + S/P-DIF Converter, Coax and Opto
Mutec	format changer advanced	digital audio format converter S/PDIF/<->AES/EBU + sample rate converter
Mutec	format changer multichannel ta	digital audio format converter TDIF/<->AES/EBU + sample rate converter
RME	ADI-6432 R	AES/MADI - converter
RME	ADI-648	ADAT/MADI - converter
RME	ADI-8 DD	8- channel AES-ADAT/TDIF bidirectionel converter
RME	Digiface	8- Channel digital IO- Unit
RME	MADI Router	In- and AOutput:MADI - Koaxial BNC, 75 Ohm, Optical Duplex SC 62.5/125 und 50/125 Multimode, Twisted Pair RJ45
RME	Micstasy	24-Bit/192kHz 8-Kanal Full Range Hi-End Mic/Line Preamp und AD-Converter
Sonifex	RB-ADDA	A TO D AND D TO A CONVERTER
Sonifex	RB-BL2	
Sonifex	RB-DA6	
Sonifex	RB-DDA6W	6 Way Word Clock Distribution Amplifier
Sonifex	RB-SC2, Dual Sample Rate Converter 24 bit 192kHz (1U)	
t.c. electronic	Konnekt 48	Firewire Audio Interface
Yamaha	AD 824	mic-preamp with AD-converter, for DM2000 or DME32
Yamaha	AD8HR analog-digital Microphon Preamp	8-ch. mic-preamp, AES-outputs, 24bit
Yamaha	AD 824 - 8-channel 24-bit DA Converter	Digital - analogue converter 8 channel , compatible with a range of digital audio formats. Precision 24-bit DA converters deliver 8 channels of high-quality analogue audio output. The DA824 can be used in conjunction with other digital audio equipment or as a stand-alone converter. It can be connected to digital mixers, digital mixing consoles or digital multitrack machines via a mini-YGDAI card slot, providing a high-quality downstream
Yamaha	Rio3224D	Stagebox for Dante-Audio-Network, 32 Mic/Line in, 16 Line out, 4 AES out
Yamaha	RMio64-D	Dante <-> MADI Converter with SRCs

Manufacturer	Item	Description
Telco - Interfaces		
AVT	Binatone compact telefon	
AVT	Magic ISDN	X.21, BRI/ISDN, LAN , G.711, G.722, PCM16, PCM20, PCM24 , ISO/MPEG Layer 2 or Layer 3 Encoder ISO/MPEG Layer 2/3 Decoder, incl. AES/EBU Option
AVT	Magic ISDN	Telephone Hybrid Call-in System for 2 ISDN S0 Busses, incl. Magic Touch Software
AVT	TH2 ISDN Telephonehybrid	digital telephonehybrid for POTS-lines or ISDN
DeTeWe	ISDN-terminal adapter	ISDN into 2 analog lines
Diverse	ISDN tester	S0 Buss Tester
Diverse	Binatone compact telefon	fits on telephone- hybrids
Mayah	Centauri 3001 III ISDN Audio Codec	ISDN codec, all standards
Prodys	Prontonet	supports Apt-X, MPEG AAC LC/LD & HE amongst its coding algorithms and bidirectional uncompressed audio transmission via IP
Sonifex	CM-TBU Telefonhybride	Line Powered telephon balance unit, 4 wire-2 wire converter.
Studer	DSP Telephonehybrid	digital telephonehybrid for POTS-lines
Multiviewer		
Decimator Design	DMON-16S Multiviewer	16x 3G-SDI / HD-SDI / SDI In Multiviewer into 1x 3G-SDI / HD-SDI / SDI Out /1x HDMI Out (Typ A)
Decimator Design	DMON-6S	6in - 3G-HDSDI Multiviewer
Imagine	Predator II	Multiviewer with 12 auto-sensing Inputs (CVBS, SD-SDI, HD-SDI), LTC, Dual DVI Outputs, redundant Power Supplies
Imagine	PX-SXP-32X6 Multiviewer Card	Multiviewer option for Platinum & Platinum IP3 frames, featuring 16 or 32 unique 3G/HD/SD signals across 6x HDMI and 6x HDSDI outputs. Embedded audio, UMD/Tally, alarms
Imagine	QVM 6800+T Quad-Split Multiviewer Module	HDSDI Quad-Split Multiviewer Module for 6800 Rack, Cascadable at up to 24 Videos on one Output.
Routers		
Friend-Chip	digi max	AES-router 6 AES-3, 2 optical ways
Hariis	PT-AECT-IB	
Harris	GPI-32	
Harris	PM-AEBT-OB	
Harris	PM-DACT-OB	
Harris	PT-ADCT-IB	
Harris	PT-AECT-OB	
Imagine	Panacea 16X16 VOE Video-Router	1RU 16X16 Analog Video-Router, external Power supply
Imagine	Panacea 32X32 HSRI	32x32 HD / Router with reclocking
Imagine	Platinum 128x128 HD-SDI 3G	HD-SDI Router 3G, incl. redundant Controller & Router Boards, redundant Power Supplies
Imagine	Platinum PT-FR-9 incl. redundante Controller & Router Boards	HD-SDI Router 3G, incl. redundant Controller & Router Boards, redundant Power Supplies
Imagine	PM-128x128-3G9	MX 128x128 cross-point module for 9RU
Imagine	PM-ATDM16-X9	
Imagine	PT-ATDM64-X28	ATDM XPT for 64 slots audio in
Imagine	PT-FSDX8C1B IBG	Internal demultiplexer frame-sync board (incl. License PT-FSIB-OPT)
Imagine	PT-FSDX8C1D IBG Input Module	3G-SDI/HD-SDI/SDI frame synchronizer module
Imagine	PT-HS-IB+ / PM-HSR8C-IBG Input Modul	Platinum 8 HD-SDI input modul
Imagine	PT-HSR-OBG+ 8 HD-SDI GREEN OUTPUT MODULE	Platinum 8 3G/HD/SD/ASI out with options and back panel, energy efficient
Imagine	PT-MXDX-SB	Platinum Muxer/Demuxer Daughter Board
Imagine	PT-PS	Platinum 750 Watts Power Supply
Imagine	PT-RES	Platinum and MX resource controller module
Imagine	PT-SYNC	

Manufacturer	Item	Description
Imagine	PV-24C-IOG Platinum VX Input/Output Board	Platinum VX SD/HD/3G Modular 24 input and 24 output Coax Video I/O Module
Imagine	PV-24O-IOG Platinum VX Input/Output Board	Platinum VX SD/HD/3G Modular 24 input and 24 output SFP Cage Video I/O Module. excl. SFPs
Imagine	PV-288X288-3G8	The Resource/Crosspoint module is present in 4 and 8 RU frames. This module performs both Control functions as well as Crosspoint functions. The module is located in the middle of the frame and visible when the front panel door is removed.
Imagine	PV-FR-8 Platinum VX	Router with max. 288x288 Crosspoint-Board, optical or electrical In and Outputs, excl. IO- Boards (please, order seperately)
Imagine	PX-576X1024-3G crosspoint card	Platinum IP3 576X1024 3G crosspoint card
Imagine	PX-ATDM64-X28	Platinum IP3 64 slot support TDM audio Crosspoint card
Imagine	PX-FR-28 IP3 Router +1x PX-576X1024-3G Crosspoint Modul <u>available from October</u>	up to 576x1024 In-& Out with 3Gb/s , 28 RU Rack, Crosspoint Module, Sync Module, Monitoring Module, De-mux Module, 4 Power supply Modules, Without I/O Modules (please define I/O size at request) price on request
Imagine	PX-FR-EXPS	Platinum IP3 external power supply frame incl. 2x PX-PS 1500 Watts Modules
Imagine	IP3 SD/HD/3G Output Module PX-HSR16C-OBG	Platinum IP3 SD/HD/3G output module w/ 16 HD BNC back panel
Imagine	PX-HSR16O-OBG	
Imagine	PX-HSR8C-IBG	8 Inputs SD/HD/3G Module
Imagine	IP3 SD/HD/3G Input Module PX-HSR9C-IBG	Platinum IP3 SD/HD/3G input module w/ 9 HD BNC + DensiShield matrix expansion + 1 HD-BNC DA back panel
Imagine	PX-HSR9C1D-IBG	9 Inputs SD/HD/3G Module
Imagine		3G-SDI/HD-SDI/SDI input expansion module
Imagine	PX-HSRAEC-OM	3 Gb/s HD-SDI output monitoring module
Imagine	PX-PS	Platinum IP3 1500 watt power supply
Imagine	PX-RES	Platinum IP3 resource controller modul
Imagine	RCP-16X1IDE Programmable LCD Button Remote Control Panel	16-Button Router panel 1 U
Imagine	RCP-24LCD-OLED Control Panel	1RU control panel with 24 LCD buttons and OLED display and 8 function keys
Imagine	RCP-32X32IDE Programmable LCD Button Remote Control Panel	64-Button Router Panel, 2U
Imagine	RCP-48LCD-OLED Control Panel	2RU control panel with 48 LCD buttons and OLED display and 16 function keys
Imagine	RCP-CCS-1U	
Leitch	GPI-20	
Leitch	Integrator	64x64 stereo audio router (configurable)+ 32 x 32 TC layer, All In- and Outputs on TT-Phone Patchbay
Leitch	SPT-ProBel-Protokoll-Interface	64x64 stereo audio router (configurable)+ 32 x 32 TC layer
Leitch	VIA	32x32 stereo audio router, redundant power supply
network	ETH-CON	
Nevion	MCON-NBOX-VK-SL	
Nevion	SL-32XY-CP	32 Button Control Panel
Nevion	SL-3GHD3232-CP	3G-Video-Router 32x32 R with Frontpanel and Sync IN
Nevion	SL-3GHD6464-CP	3G-Video-Router 64x64 R with Frontpanel and Sync IN
Nevion	SL-HD0808-N-CP	3G-Router 8x8 BNC incl. Front Panel and Sync In
Sonifex	RB-SS10	10-way Stereo pre-amp. Alternating or mixing of sources
sono	Monitoring switcher 2x8 in 1	3U cardcage with isolating-amplifier

Manufacturer	Item	Description
USV		
APC	UPC	Uninterruptable power source, 3kVA/8 minutes
APC	SUA 3000 RMI2U	Smart-UPS 3000 VA Uninterruptable power source.
APC	SUA 3000 RMXLI3U	Smart-UPS 3000 VA Uninterruptable power source.
APC	UPC - 450W	Uninterruptable power source, 450 VA
ART Lighting	32A AL-Rackpower 2HE 6x Schuko	
BSS	Audio MSR-602 II Splitter Power Supply for MSR-604 II	
EATON	5PX 3000I RT3HE	Rack/Tower LCD USV-2700 Watt
EATON	5PX EBM 72V RT3U	
Edelstrom	MD-3000RT	
IDX	IA-200a	Stand alone 2x XLR Output Camera AC Adapter, 100W/13,8 V
IDX	IA-300a	Stand alone 3x XLR Output Camera AC Adapter, 210W/13,8 V
Imagine	Power Supply 6822+AC	
Lynx	Yellowbrik R PS 1120 EU	Redundand power supply for Yellowbrik Frame
Multimatic	MD 2-3 KVA	
Multimatic	MD 3000VA	Uninterupted Power Supply 3 KVA
Multimatic	MD- 2-3 KVA	
Multimatic	MD-3000I	
Multimatic	MD-3000I-15 (S)	3000 VA Uninterruptable power source.
Multimatic	MD-3000I-20	
Multimatic	UPS SR020T	MD-X Serie, IN 380-415V 3/N/PE 50/60Hz, 30A OUT 380/400/415V 3/N/PE 50/60Hz, 29A 20000VA/18000W
Sennheiser	L 50	charging unit (incl. external power supply)
Wisycom	PSS 22/23/25 Power Supply Module	
Test Equipment		
DirectOut Technologies	ANNA-LISA	compact mobile Test and Signal Generator for MADI
JDSU	FBP-HD4I	Fiber Inspection System Small Form-factor-Display mit 1,8-Zoll-TFT-LCD
Konika Minolta	KM CS-200, Konica Minolta Chroma Meter CS-200	The Chroma Meter 200 - portable measuring device that allows fast and highly accurate measurements of the luminance and colour of LCDs and other displays. The CS-200 light meter is equipped with a photodiode array (40 elements) that captures the spectral energy distribution of the light source and calculates it with the standardised eye sensitivity curves according to CIE 1931 to give exact colour information. The measuring range extends over the extremely wide luminance range from 0.01 cd/m ² to 20,000,000 cd/m ² .
Lynx	P TG 3610 B (Testor)	Translated with www.DeepL.com/Translator (free version) SD/HD Video and AES Test Generator (BNC)
Lynx	R CT 3602	Service Adapter for P TG 3610
Phabrix	PHABRIX Sx	Video Test Signal Generator, Monitor & Audio/Video/Data Analyzer 3G-SDI, HD-SDI and SD-SDI portable Eye Pattern & Jitter Analyzer,
Phabrix	SxTagc	Sx TAG with its SFP, SDI and analog I/O offers incredible versatility in a handheld device. It is ideal for IP, 3G/HD/SD-SDI, optical SDI, HDMI and Analog test & measurement as well as AES eye analysis, for applications demanding true mobility and ease of use. It provides support for SMPTE ST 2110-20/30/40 encapsulation/decapsulation with ST 2059 PTP, SDP and NMOS as well as SMPTE ST 2022-6 encapsulation/ decapsulation, using 10GE IP SFP+ modules developed by Embrionix.
RTW	31960 SD	
RTW	TM3	4,3" Touch Screen, Loudness-, True Peak- und PPM-Meter

Manufacturer	Item	Description
RTW	RTW, TM7	7" Touchmonitor - Audio Loudness Measurement with HD-SDI Option
RTW	RTW, TM9	PeakMeter Loudness, (Multichannel Mode, Loudness/ u.a R128, Radar).
Schomandl	FIT RF- Testing Kit	Case with Base-Unit, Testing-Head, Adapters
Sonifex	RM-4C8 incl. HD1 Reference Monitor	With 4 x bright high-resolution 26 segment meter displays and separate left and right source selectors, the RM-4C8 is ideal for monitoring audio channels in an SDI group, or groups of de-embedded AES/EBU channels.
Sonifex	RM-4C8 Reference Monitor	With 4 x bright high-resolution 26 segment meter displays and separate left and right source selectors, the RM-4C8 is ideal for monitoring audio channels in an SDI group, or groups of de-embedded AES/EBU channels.
T&S	AMS17HDM digital monitoring unit	The monitoring unit is built into a compact 19", 1U housing and features two digital AES/EBU audio inputs (XLR fitting) as well as an internal HD/SDI audio deembedder with access to all 16 audio lines that can be transmitted in the digital video stream.
Tektronix	PRISM WFM	Plattform for IP/SDI-Real-time analysis
Tektronix	WFM 2200	3G/HD/SD-SDI Waveform Monitor/Generator
Tektronix	WFM 5000	SD/HD Waveform Monitor
Tektronix	WFM 5250	3G/HD/SD/SDI/HDMI Multiformat Waveform Monitor
Tektronix	WFM 700	HD/SD-SDI Waveform Monitor
Tektronix	WFM 7120	HD Waveform & Vector Monitor, Eye-Pattern, Jitter, Quad Display Mode
Tektronix	WFM 8200 4K	
Tektronix	WFM 8300	3G HD Waveform & Vector Monitor, Eye-Pattern, Jitter, Quad Display Mode
TSL	PAM2-3G16-MK2	16 Channel Audio-Video-Monitor, 3G, Dolby D/E, 2HE, 2x 3G HD/SD-SDI, 8x AES, 6x stereo.
TSL	PAM2-IP	Video and Audio Monitoring for HDSDI & SMPTE 2022-6 and SMPTE 2110 networks
Vistek	HD VALID8 V6811/12	Audio-Video Delay Messurement-Generator
Vistek	HD VALID8 V6811/12	Audio-Video Delay Messurement-Reader
Vistek	VALID 8 HD V6811/12 V6821/22	Audio-Video Delay Testing Generator / Receiver
Wohler	AMP-2	monitoring unit, 10 selectable stereo-sources, balanced AES3 input with loopthru
Wohler	AMP1-E16-3G	1RU, the AMP1-E16-3G with Dolby monitors 16 channels of audio from 3G/HD/SD-SDI, Dolby D or E, and AES sources with level meters configured and displayed on two of three OLED screens. A third screen is dedicated to displaying diverse data or video de-embedded from the selected 3G/HD/SD-SDI input.
Wohler	AMP2-S8	digital /analogue monitoring unit 2RU,19": 8x analog line In, 4x digital (AES/EBU) 75Ω BNC 4x digital (AES/EBU) 110Ω, 2x SDI, embedded 75Ω BNC, individual selection of all inputs to L+R monitor outputs, 8x 53-segment display (VU oder PPM), phase indicator
Wohler	AMP2-S8-MDA Audio Monitor	8 Channel, 3G/HD/SD-SDI, Audio Monitor, 2RU
Wohler	AMP2-S8MDA	digital /analogue monitoring unit 2RU,19": 8x analog line In, 4x digital (AES/EBU) 75Ω BNC 4x digital (AES/EBU) 110Ω XLR, 2x HD/SDI, embedded 75Ω BNC, individual selection of all inputs to L+R monitor outputs, 8x 53-segment display (VU oder PPM), phase indicator
Wohler	TFT-Display	19" 3U, 3 displays
Wohler	TFT-Display	19" 3U, 3 displays

Manufacturer	Item	Description
Wohler	MON4-2W/HR	4-Display HD-SDI Monitoring, 2 HE
Wohler	VM-4	monitoring unit, 4 inputs, individual volume control, 1U
Controller Systems		
Blackmagic	GPI and Tally Interface	Blackmagic Design GPI and Tally Interface; GPI and Tally Interface for Atem production switcher; With 8 Contact closure tally outputs, tally signals can be send to your cameras, replay machines and monitors, so everyone knows which camera is 'on-air'; if more tally outputs are required, several GPI and Tally interfaces can be linked together, because it connects via Ethernet to an ATEM production switcher; Connections:; Contact Closure: 25-pin D-Type connector provides 8 opto-isolated inputs and 8 relay Contact closure outputs; Computer interface: 1 USB 2.0 high-speed connection for configuration and product software updates; Inputs: Optical isolators
JLCooper ELECTRONICS	Ebox	
Lawo	Comserver Dual	Dual Interface TCP/IP-RS422
Lawo	UMD	Display-Dual-Proxy TCP/IP-RS422, 19 inch
Lawo	UMD SD 1/2 19"	
Lawo	UMD	Display-Single-Proxy TCP/IP-RS422, 19 inch
Lawo	UMD-SD 19"	UMD-SD 19"
Lawo	VSM GPI/O Interface	32 input / 32 output
Lawo	VSM LBP - 16e BL	16-Button-panel with Incremental-encoder
Lawo	VSM LBP - 17 BL	17 Button-Panel
Lawo	VSM LBP - 17 SI	17 Button-Panel
Lawo	VSM LBP - 24 SI	24-Button-panel with Incremental-encoder
Lawo	VSM LBP - 31e	31-Button-panel with Incremental-encoder
Lawo	VSM LBP - 32	32 Button-Panel
Lawo	VSM LBP - 50e BL	50-Button-panel with Incremental-encoder
Lawo	VSM LBP - 51 BL	51-Button-panel
Lawo	VSM LBP - 51 SI	51-Button-panel
Lawo	VSM Server	Licenses incl.
sonoVTS	VSM GPI 32In/32Out XLR Auflösung	
Wireless Systems - Accessories		
Garmin	GPS16x-HVS	
IDX	DUO-C190 Li-Ion Battery	
IDX	VL-4S Li-Ion Battery Charger	
Procom	GPS 2000W-TNC	
Sennheiser	A 1031-U	passive omnidirectional antenna frequency range 450 - 960 MHz
Sennheiser		
Sennheiser	A 9000 630-798 MHz	
Sennheiser	A12AD-UHF 790-814 MHz	
Sennheiser	AC 3200, Antenna-combiner	active 8-channel transmitter combiner for in ear-monitoring, 500 - 870 MHz
Sennheiser		
Sennheiser	AD 3700	active RF-Antenna 470-866 MHz
Sennheiser	AD 9000 630-798 Mhz	
Sennheiser	ASA 9000	Antenna-combiner for Sennheiser Digital 9000
Sennheiser	B 250	batterypack for SK 50
Sennheiser	B 50	batterypack (2 cells) for SK 50
Sennheiser	B 5000	batterypack for SKM 5000
Sennheiser	BA 250	accupack for SK 50
Sennheiser	BA 50	accupack (small) for SK 50
Sennheiser	BA 5000	accupack for SKM 5000
Sennheiser	EK 2000 IEM	Stereo Diversity Receiver 626 - 698 MHz
Sennheiser	EK 2000 IEM	Stereo Diversity Receiver 718 - 790 MHz
Sennheiser	EK 300 IEM	Evolution Wireless In Ear System Freq.Range-B: 626-668 MHz

Manufacturer	Item	Description
Sennheiser	EK 6042 470 - 654 MHz	Two-channel ENG receiver. Connectable to every Sennheiser wireless system – analog or digital. Switching bandwidth of 184 MHz
Sennheiser	EM 1046 channel 61-63	8-ch. wireless-receiver, UHF, 19", 4U
Sennheiser	EM 3031	1-ch. diversity receiver, UHF, 19", 1U
Sennheiser	EM 3732 Multichannel receiver	2-channel UHF diversity receiver, 90 MHz switching bandwidth, 779 -866 MHz, multiband compander, 19" 1U,
Sennheiser	EM 9046 Wireless microphone system	8 Channel Receiver-Frame. Fully - Digital transmission 470-798 MHz
Sennheiser	MMD 935	Dynamic cardioid microphone capsule, Color: black
Sennheiser	SK 50-UHF channel 61/63	bodypack transmitter, 50mw
Sennheiser	SK 5212 bodypack transmitter 782-818 MHz	bodypack transmitter, 50mW
Sennheiser	SK 9000 630-718 MHz (B1-B4) Pockettransmitter	Digital Wireless-Pockettransmitter
Sennheiser	SK 9000 Wireless-Pockettransmitter 710 -798 MHz (B5 - B8)	Digital wireless pocket transmitter. Frequency range 710-798 MHz, (TV channel 51 - 60) B5-B8
Sennheiser	SKM 9000 Microphone 710-798 MHz (B5 - B8)	Digital wireless handheld transmitter. Frequency range 710-798 MHz, microphone capsule KK204 nickel
Sennheiser	SPA114/2	Antennen-Combiner/ Distributer 2X 1in4
Sennheiser	SR 2000 IEM 718 - 790 MHz	In-ear-monitoring Transmitter 718 - 790 MHz
Sennheiser	SR 2000 IEM BW-X	In-ear-monitoring Transmitter 626 - 698 MHz
Sennheiser	SR 300 IEM G3 - B	Evolution Wireless In Ear transmitter, Freq.Range-B: 626-668 MHz
Sennheiser	SR 3254-U Stereo transmitter 830 - 866 MHz	in-ear-monitor transmitter, Stereo, HDX compander
Shure	UA840A-MA-UHF	antenna distribution amplifier
Vislink	Fanbeam directional antenna GA-FB13 -3.5R	
Vislink	FocalPoint Camera Control Interface Unit CRIU-ASSY-7004	
Vislink	FocalPoint Telemetry Outdoor Unit FCDT-ASSY-7010	
Vislink	L1244 4x Antennansplitter	
Vislink	L1700 & L2194 Antenna Set	Consists of: - 4x L3530 omnidirectional antenna (for L3025) - 1x L3430 omnidirectional antenna (for L1700) - 1x telemetry groundplane antenna (for FocalPoint telemetry transmitter) - 2x telemetry omnidirectional antenna (for L1700)
Vislink	L3025-3239E Down-Converter	Antenna Input: N-Type (F) 50Ω UHF Output: BNC (F) 75Ω Noise Figure: <3dB* Phase Noise: -90dBc/Hz @ 10kHz offset Spurious: <-60 dBm O1P3: >26 dBm OP 1 dB: >14 dBm Image/Half-IF Rejection: >60dBc
Wisycom	ABN10-32 Booster	
Wisycom	AGN 10 60-64	
Wisycom	BAN	
Wisycom	CST 910	stationary diversity base-station with portable transmitter/receiver
Wisycom	LBN	Antenna
Wisycom	LBN-A	
Wisycom	MCR 34 L Ch. 61-64	diversity camera-receiver, batterie-or extern-powered. 784-817 MHz. 32 frequency -pre-sets
Wisycom	MCR 40 / 590 - 622 MHz	Diversity Camera-Receiver
Wisycom	MCR 40 / 742-773 MHz	Diversity Camera-Receiver
Wisycom	MCR 40 / 784-818 MHz	Diversity Camera-Receiver
Wisycom	MCR 42 / 590 - 822 MHz	Dual Diversity Camera-Receiver
Wisycom	MRK 920 Rackframe	8 channel receiver frame, 4U 19"

Manufacturer	Item	Description
Wisycom	MRK 950 Dual receiver 630 - 870 MHz	modular wireless-microphone receiver system 19" 1U module, stackable, with dual true diversity receivers, tuning windows of 240 MHz with tunables filters (2 ch's independent)
Wisycom	MTH300 microphone B6 770 - 870 MHz	UHF handheld transmitter with Schoeps capsule MCM301, 50mW, 770-870 MHz, display, switching bandwidth 12 TV channels, power supply 2xAA (Mignon)
Wisycom	MTK 952	Two-channel in-ear-monitoring transmitter 470 - 800 MHz, 10mW -200mW.
Wisycom	MTP 22 L Ch. 55-58	bodypack transmitter, 50mW ERP, 32 Frequenz, 470-880 MHz
Wisycom	MTP 22 L Ch. 60-64	UHF pocket-transmitter, 50mW ERP, 32 frequencies, 784-817 MHz
Wisycom	MTP30 bodypack transmitter B4 630-750 MHz	UHF pocket transmitter, 50mW, 630-750 MHz, display, power supply 2xAA (Mignon),
Wisycom	MTP30 bodypack transmitter B5 700-800 MHz	UHF bodypack transmitter, 50mW, 700-800 MHz, display, power supply 2xAA (Mignon)
Wisycom	MTP30 bodypack transmitter B6 770 - 870 MHz	UHF bodypack transmitter, 50mW, 770-870 MHz, display, power supply 2xAA (Mignon)
Wisycom	MTP30-L-B3 560 - 660 MHz	
Wisycom	RBK	receiver for Wisycom/Sennheiser wide-band systems, 32 frequencies, diversity- antennas
Wisycom	RPU/RBK 300-reporter system	stationary diversity base-station with portable transmitter/receiver
Wisycom	SPA6-2A 784-818 MHz	active antenna- combiner, 3x2 input, 1x2 output
Wisycom	SPL 214A	19" 1HE, 2x 1 in 4 Antenna Distribution
Wisycom	SPL 214AW	19" 1HE, 2x 1 in 4 Antenna Distribution 470-870 MHz
Wisycom	SPL 218AW	19" 1U, 2x 1 in 8 Antenna-Distribution

Commentator / Interpreter Units

Ambient	Accupack	enclosure for NP-1-type rechargeable batteries
Glensound	GS-GC5/G ISDN Mixer Workstation	ISDN commentatorunit, MPEG layer2, G 722 and APTX standard, mains or battery powered
Glensound	GSOC33	base unit for 10 x GSOC34 commentary unit
Glensound	GSOC34	commentary unit for GSOC33 base unit, 2 headsets Beyer DT 290
sono	wiring of commentary equipment	ISDN wiring (S0-Bus), HF wiring and splitting
sonoVTS	Commentary Equipment	ISDN commentaryunit, (Glensound, 2 headsets Beyer DT 290) and 17" display
Zähl	AIRCUM	Commentator unit for two commentators + one guest, 3 CH intercom, GPI/O, remote-function, 12-24V, PSU included
Zähl	AIRCUM-IR	Interpreter remote for AIRCOM
Zähl		
Zähl	CSX-11, Series 2	Commentary add-on for Riedel DCP- Panels

Intercom Digital

Riedel	Artist 128	digital Intercom matrix 1024x1024, hot swap of all modules, redundant power supplies, redundant node controller, ports for control panels or 4 wire IO's
Riedel	Artist 64	digital Intercom matrix, hot swap of all modules, redundant power supplies, redundant node controller, ports for control panels or 4 wire IO's
Riedel	Client Card AES-108	Digital Audio Client Card, 4x AES3 on RJ45, incl. Backplane
Riedel	Artist Client Card AIO-108	8x 4-wire analogue Audio Client Card, 8x RJ45, incl. Backplane
Riedel	Artist Client Card COAX-108	8 Control Key-Panel Client Card, 8x BNC, incl. Backplane
Riedel	Artist Client Card GPI-116	16x GPI (TTL), 16x GPO (open collector) Interface Card on 2x SubD37
Riedel	Artist Client Card MADI-108	
Riedel	Artist S - MFR 200	digital Intercom matrix 32x32 ports for control panels or 4 wire IO's

Manufacturer	Item	Description
Riedel	BL-ANT-1010-19G-EU G2	Active cellular antenna for Bolero Standalone and Bolero Integrated, European version (grey) with E-Ink display for up to 10 BL-BPK-1006-19 beltpacks. Licence-free DECT frequency band (1880-1900 MHz); AES67 Layer 3 IP network mode via CAT5 cabling; optional standalone daisy chain network mode via CAT5 cabling; PoE+ (802.3at, type 2, class 4, 15-30W); Power supply, local DC power supply unit or decentralised PoC daisy chain power supply.
Riedel	BL-ANT-APP-STANDALONE	Standalone authorisation for a Bolero antenna. Allows you to switch antennas in the Bolero network in standalone mode. (It will require one licence is required per network)
Riedel	BL-BAT-1015-ST Li-Ion Bat.	Rechargeable lithium-ion battery 15Wh for BL-BPK wireless beltpack, charge status telemetrically scannable, more than 15 hours of use in BL-BPK belt pack
Riedel	BL-BPK-1006-19-EU	6-button digital wireless roaming beltpack European version. Licence-free DECT frequency band (1880>1900 MHz), rotary knobs for setting master and individual volume, reply button, call light, sunlight-readable full-colour LED display, ADR receiver, NFC, BT, 4-pin XLR headphone jack, robust housing with rubberised protective surfaces and internally integrated antennas. Includes 1 x BL-BAT rechargeable lithium-ion battery. Headset not included
Riedel	BL-CHG-1005-R	Translated with www.DeepL.com/Translator (free version) Table or wall charging station with 5 charging places for BL-BPK or spare battery BL-BAT, network-compatible, built-in universal power supply
Riedel	BL-EPS-1001-00 Bolero	Bolero External power supply for a single BL-ANT antenna. Required when PoE is not available
Riedel	Artist S (M) - DCP 1008 E	desktop-control panel, LCD, 8 keys
Riedel	DCP 1016 E	desktop control panel, 16 keys
Riedel	DCP-2116 P	
Riedel	ECP 1016 E	16-Button LED 19" Expansion Panel
Riedel	ECP 1116 OLED	16-Button OLED 19" Expansion Panel
Riedel	Riedel FBI 1310 SM	Fiber Interface Adapter. converts an Artist panel port matrix from CAT5 to optical fiber
Riedel	RCP 1012 E	control panel, 12keys, 19" / 1 RU
Riedel	RCP 1028 E	control panel, 28 keys, 19" / 2 RU
Riedel	RCP 1112 OLED	12-Button OLED 19" Control Panel
Riedel	RCP 1128 OLED	28-Button OLED 19" Control Panel

Intercom Analogue

Canford	Stereo Headphone Amp.	beltpack headphone preamp, 9V DC
Canford	Stereo Headphone Amp.	beltpack headphone preamp, 9V DC
Clear-Com	FL-1	CALL-signalisation via flash or ringtone
Clear-Com	IFB4B	2/4-wire interface for Clearcom beltpacks
Clear-Com	MS 232 Beltpack Intercom Basisstation	basestation for 2 beltpack-rings, aux- input and page-output
Clear-Com	RS-501 Beltpack	beltpack for 1 intercom ring, mic on/off switch, signal button and indicator, volume control, sidetone adjust, and 4-pin headset connector. Connects with 3-pin intercom and loop-through connectors.
Clear-Com	RS-601 Beltpack	beltpack for 1 intercom ring
Prospect	AMM 10	10-ch. monitoring unit, speaker and phones mode
Prospect	C6 LXT Kdo.Matrix	6x6 intercom-matrix, configurable via DIP-switches
Prospect	C6 LXT/ 6 Beltpack-Matrix	6x6 intercom-matrix for up to 5 beltpacks and 1 4-wire-port, configurable via DIP-switches, cabling is arranged in a star configuration with 2 audio pairs/beltpack
Prospect	C6R	6 Way, 4- wire intercom

Manufacturer	Item	Description
Prospect	IFB 10M	10-ch. IFB-talkback unit
Prospect	K6R	6 Channel 4-wire Intercom - Panel
Prospect	VM10 ML	10 ch. line identification unit
Riedel	IF2004	2/4-wire interface for beltback-rings
Sonifex	RB-PMX4 Preset-Mixer	10 Input, 4 Output Analogue Preset Mixer
sono	10-2-10	summing/distribution amplifier, merging 10 4-wire comm signals to 2 busses
Whirlwind	Qbox	Audio Mic/Line Tester / Cable/Test Tone Generator
Zähl	AIB-1	Beltpack, for use as a 4-wire Talkback-unit, Headphone-amp (stereo), Mic-pre-amp. powered with 2 AA-size batteries.
Zähl	AID 1	analogue Intercom for 1 4-wire. IFB Function und Programm-in
Zähl	AID-6	analogue intercom-unit, 6x 4-wire talkback channels, 2 IFB-busses, interpreter mode, mic/headset use, external power-supply incl. PSU
Zähl	AIR-4	analogue rack intercom-unit, 1RU, 4x 4-wire talkback channels, 4 IFB-busses, mic/headset use, external power-supply incl. PSU
Zähl	AIR-8	analogue rack intercom-unit, 1RU, 8x 4-wire talkback channels, 4 IFB-busses, mic/headset use, external power-supply incl. PSU
Zähl	ASD-8	8-channel Matrix. +/- 15dB gain-range on In- and Output.
Slow motion & HD-Recorder		
EVS	HD XT2	6-channel Livemotion-System
EVS	HD XT2 (super)	Livemotion-system, 6-channel Harddiskrecorder
EVS	HD XT3	HD-Livemotion-System, 6-Channel Harddiskrecorder
EVS	HD/SD XT2 (super)	6-channel live-motion-system
EVS	SD XT1	6-channel live-motion-system
EVS	EVS, X-Hub	
EVS	XFly	XFly portable NAS storage with internal RAID5 8x1TB SATA 2.5" Compact, portable frame with 8x1TB hot swap 2.5" SATA HDD
EVS	XT SD	6-channel livemotion system
Grass Valley	K2 Media Server & Storage Platform	K2-XDP-4HD, HD Video Server, 4 Channels, Internal HDD Storage 8 -600GB, AppCenter Pro License. DVCPro HD
Timecode Equipment		
Alpermann & Velte	AT Modul	
Alpermann & Velte	AV TC30G	timecode generator, incl. power-supply
Alpermann & Velte	AV TC30RI	timecode reader/ins, incl. power-supply
Alpermann & Velte	GL Modul	Master Time Code, Timer and Time Generator (LTC)
Alpermann & Velte	HT Modul	Timecode Reader / Generator / Converter and Inserter on digital Video, LTC, RS485, RS422,RS232, D-VITC,
Alpermann & Velte	IE Modul	NTP Client
Alpermann & Velte	MTD D56	LED Timecode Display
Alpermann & Velte	RUBIDIUM Series 1	
Alpermann & Velte	TCU	Timecode Controller, Up-/Down-timer
Alpermann & Velte	UD25L	
Alpermann & Velte	UD25L	
Alpermann & Velte	UDD 25L	Dual MTD Timecode Display 19", 1U
Ambient	Clockit Controller ACC101	clockit master controller, 6 receiver with timecode +videosync output
Ambient	Lockit Timecode ACL 201-II	portable timecode generator
C-Lab	Time Machine 1.1	universal clock converter / masterclock

Manufacturer	Item	Description
Leitch	DTD-5225	Digital Clock The DTD-5225 is an LED digital clock with 7-segment-digits display. It may operate as a time-code-reading clock or as a digital SMPTE/EBU serial time code reader, simply displaying the input time code. In addition to SMPTE/EBU time code, the clock can operate on the internal quartz time base, or from the 50/60 Hz power line. This three-way reference capability allows easy integration into new or existing clock systems.
Rosendahl	MIF 3	MTC-LTC Interface
Tektronix	TG ECO 422 Change over Unit	has 11 user configurable channels with primary and back-up I/O Amp detection on all channel
Tektronix	ECO 8000	Changeover unit for SPG 8000
Tektronix	SPG 8000	Master Sync & HD-SDI Signal Generator
Tektronix	SPG 8000	Master Sync & HD-SDI Signal Generator
Tektronix	TG 700	Master Sync & HD-SDI Signal Pattern Generator
Splitter / ADA		
AB	DA2148A	distribution amplifier 1 in 8 / 2 in 4
Accessit	AR 116	DI-box
Audionics	Distribution Amplifier 10 out's	distribution amplifier 1 in 10
BSS	AR 116	active DI-box
BSS	MSR 604 Mic/line split system	The MSR-604 II is a professional mic/line split system. Per unit, four inputs can be distributed to two electronically balanced outputs each for FOH and monitor and two further transformer-balanced outputs (recording, OB van, etc.). Each input channel offers up to +20 dB gain, phantom power and the possibility of monitoring the channel signal via headphones using the MSR-602 II power supply.
Canford	Line-isolation transformer	mono
Canford	Line-isolation transformer	stereo
Diverse	FBAS distributor	
Klark Teknik	DN1248 Plus DP 12 Input, 48 Output Mic-Splitter	active mic-splitter, 12 channel, XLR connectores, 1 in 4 split, 2 electronically balanced and 2 transformer balanced outputs, two power supplies
Klark Teknik	LBB 100	active DI-box
Lake People	AED F62	2x 1in4 AES distribution amp
Lake People	F12 Sym-Amp	2 stereo unbalancing units, 3 stereo balancing units
Lake People	F15 Matchbox	8-ch. balancing unit
Leitch	FR- 884	12x 1in7 distribution amp
Lundahl	Line-isolation transformer	stereo
Palmer	PPB 20	press box mic / line splitter 1 in 20
Palmer	PPB 20	press box mic / line splitter 1 in 20
Pikatron	Video isolating transformer	
Proco	IT8	8-ch. line-isolation transformer, 1HE
Procom	PRO-RPS-2-N	
Sennheiser	ASP 113	
Sennheiser	ASP 212	
sono	Line-isolation transformer	16 way balanced - unbalanced converter with transformer, adjustable, 1U 19"
sono	10 ch. ADA	10 x 1 in 8 distribution amplifier, flightcase, in/outputs TT-phone jackfield
sono	Line-isolation transformer	
sono	Line-isolation transformer	balanced to unbalanced converter, stereo, adjustable
sonoVTS	Line-isolation transformer	
sonoVTS	Line-isolation transformer	
sonoVTS	XLR-Y-Box	
Whirlwind	HotBox	active DI box

Manufacturer	Item	Description
DJ equipment		
Pioneer	CDJ 1000Mk2	CD player with smart-media-slot
Pioneer	DJM 600	DJ mixer
Vestax	PDX 2300 MKII PRO	DJ-turntable
Control Room Speakers		
Fostex	6301 BX	active speaker
Fostex	6301ND	20 watt power amplifier Mounting: 10 cm full range speaker frequency range: 75 -15.000 Hz balanced AES/EBU interface and unbalanced jack input magnetically shielded housing
Fostex	RM-2	active rack speaker
Fostex	RM-3	Stereo Rack Monitor
Genelec	1029 A Speaker	control room monitor, 2-way active (40+40w)
Genelec	5.1 surround set	set of five 8050A DSP, subwoofer 7071A DSP. Autocal™ - calibration-algorithm
Genelec	7050CPM Subwoofer	For 2.1 to 5.1 setups Class D power amplifier 130 W Transmission range: 24 - 85 Hz (-6 dB), 24 - 120 Hz (LFE) Maximum level: 103 dBSPL / 1 m briefly in the half-space (averaged 30 - 85 Hz) Speaker: 205 mm Chassis Bass management with integrated filtering for the connected speakers Switchable filters for adaptation to room acoustics Connections: 5 x line input XLR
Genelec	7271A DSP	sub-woofer for surround-setups. with Autocal™ - calibration-algorithm
Genelec	8030A	2 x 40W Aktive Studio-Loudspeaker 5" / 3/4"
Genelec	8030B	Aktive Studio speaker 5" / 3/4", analogue & digital Inputs
Genelec	8030CP Speaker	Active 2-Way Studio Monitor Linear frequency range: 54 Hz - 20,000 Hz (+/-2 dB) Maximum SPL: 110 dB (peak per pair with music material at 1 m distance) 5" Woofers 3/4" Metal dome tweeter with DCW Bass reflex housing made of aluminium Amplifier output: 50 W + 50 W Active crossover and effective protection circuits On/Off automatic
Genelec	8250A DSP Speaker	nearfield- / midfield-monitoring for broadcast, OB-van's and surround-setups. with Autocal™ - calibration-algorithm
Genelec	AutoCal	Loudspeaker Manager Software
Klein & Hummel	MM 201	active speaker
Klein & Hummel	MM 402/TV	control room monitor, active
Klein & Hummel	O 198	control room monitor, 3-way active, 1x8", 1x3", 1x1", 112 dB
Köln-ton	CS 360 Speaker	omnidirectional speaker system, 360°
Neumann	KH 310 D R	Three-Way Active Studio Monitor (left)
Neumann	KH 310 D L	Three-Way Active Studio Monitor (right)
Neumann	KH 805 G	Active Studio Subwoofer
PreSonus	Eris E5 Speaker (available as of October)	speaker, 2-way active, 5.25" woofer with composite membrane 1" tweeter with silk dome, 80 Watt Class-AB Bi-Amping Power Amplifier, Bass reflex opening on the front for outstanding bass reproduction, Acoustic tuning functions a precise mixing environment: midrange (±6 dB, stepless) / height range (±6 dB, stepless) / high-pass filter (off, 80 Hz, 100 Hz)
Yamaha	MSP3 Speaker (available as of October)	100mm woofer - 22mm tweeter - 20 Watts RMS - max. SPL 98dB
Yamaha	MSP5	control room monitor, 2-way active, 1x5", 1x1", 101 dB

Manufacturer	Item	Description
Tripods - Accessories		
	D-shackles	
	Transpor case	
	Windshield small	
	Windshield small	
audio-technica	Soft-Zep Windcover and Pistol Grip	
d.T.C	Alutruss 4-Punkt-Traverse	
Despar	Drop-Arm 0,5-1m	
Despar	Drop-Arm 1-2m	
Despar	Tube hook	for standard lighting tubes up to 60mm, with "TV"-spigot
Despar	Safety Bond	with carbine hook on both ends, Length app. 1m
Diverse	Aero-Studs	
Diverse	Safeties, nylon, short	
Diverse	Safeties, nylon, long	
Diverse	Music stand light	
Ergotron	Display Wall Mount »TM«	Tilting Wall Mount for LCD-Displays, minimum 32"
Ergotron	Neo-Flex 45-174-300 monitor bracket	Stepless height adjustment of 203mm, load capacity up to 8.2kg, VESA bracket standard 75x75 and 100x100mm compatible
Kobold	Speaker Stand large with "TV" spigots	
König & Meyer	26720 Monitor stand	Bearing plate: 245 x 205 mm EAN: 4016842816224 Height: from 680 to 1,140 mm Height adjustment: locking screw and safety pin Leg construction: fixed screw-in legs Material: steel Max. load capacity: 35 kg Product Category: Topline Rod combination: 2-piece folding design Special features: internal cable routing possible; support plate with
König & Meyer	26782 Display Stand	
König & Meyer	Fishpole	
König & Meyer	Mic-Stand large	with balance weight
König & Meyer	Mic-Stand large, 3m	black finish, without boom, 3/8" thread
König & Meyer	Speaker Stand large	black, height: 1355/2180mm
König & Meyer	Speaker Stand small	Black, height: 1005/1545mm
König & Meyer	Speaker Stand with hand crank	black, hand crank, height: 1355/2180mm
König & Meyer	SG 20, stand clamp	for CMC 6
König & Meyer	Mikrophon Stand small	boom arm
König & Meyer	Mikrophon Stand standard	black, boom arm
König & Meyer	Mikrophon Stand 210/9 3/8"-Gew schwarz	A more compact version of the classic 210/2. The combination of the long-legged 201A/2 mic stand and the 211/1 telescopic boom arm. Like the 210/2, the 210/9 sets the standard for professional microphone boom stands.
König & Meyer	Mikrophon Stand 259	Low-level, telescopic stand with foldable legs. Comes with 2-piece boom arm.
König & Meyer	Mikrophon Stand grey	grey-finish, boom arm
König & Meyer	Mic-Stand extension 1000mm	
König & Meyer	Stereo-Mikrophon bar	347mm or 173mm-length
König & Meyer	Round base 130mm	Black, with extension and boom arm
König & Meyer	Round base 180mm	Black, with extension and boom arm
König & Meyer	Round base 250mm	Black, with extension and boom arm
König & Meyer	Mikrophon Stand standard	Cast-iron round base, with anti-vibration rubber insert for noise filtration. Attractive gray Soft-Touch powder coating.

Manufacturer	Item	Description
König & Meyer	black cast-iron base	for goosenecks, horizontally mounted XLR-style female socket
König & Meyer	Table Tripod	
König & Meyer	carbon fibre boom	95 cm - 3,2 m
König & Meyer	Universal clamp	
König & Meyer	Microphone Holder	Universal microphone holder with 3/8" Thread
Manfrotto	Manfrotto Magic-Arm	incl. clamp and 3/8" thread
Neumann	EA 21 elastic suspension	
Neumann	MF 2	table-stand
Neumann	MF 3	table-stand 110mm
Neumann	SG 21 / 17	swivel mount
Neumann	system case KM100	4 pc. KM100 incl. accessories and capsules
Quikpole	QP 4140 carbon fibre boom	1,50 m - 5,4 m
Quikpole	QP 460 carbon fibre boom	75 cm - 2,4 m
Quikpole	QP 565 carbon fibre boom	75 cm - 2,4 m
Rycote		
Rycote	stereo M/S - X/Y application with windshield	stereo microphone arrangement
Rycote	Windshield for KMR 81	
Rycote	Windshield for KMR 82	
Rycote	Windshield for KMR 81	incl. windjammer (furry cover)
Rycote	Windshield for KMR 82	incl. windjammer (furry cover)
Schoeps	A 2o, elastic suspension	for CMC 6
Schoeps	BF 250, Base	black, for CMC 6
Schoeps	MAB 1000	OCT (optimized cardioid triangle) -surround-array
Schoeps	HC, collette clamp	for CMC 6
Schoeps	IRT-Cross CB 250	surface finish: anthrazith
Schoeps	KC 5g -Colette cable	5m
Schoeps	MAB 1000	OCT (optimized cardioid triangle) -surround-array
Schoeps	R2C 350 KC 0,5 g , Double Tube	twin version of the RC KC colette surface finish: matt gray
Schoeps	RC 1200lg, active stereo tube	surface finish: matt gray
Schoeps	RG 8, stand connector	for connecting two STR vertical support rods
Schoeps	RG 88, stand connector	for connecting two STR vertical support rods
Schoeps	SG 20, stand clamp	for CMC 6
Schoeps	HC, collette clamp	for CMC 6
Schoeps	SM 270 special foam mat for BF 250	additional isolation against vibration for BF 250
Schoeps	STR 250g, vertical support rod	surface finish: matt gray
Schoeps	STR 350g, vertical support rod	surface finish: matt gray
Schoeps	STR 600g, vertical support rod	surface finish: matt gray
Schoeps	STR1000g, vertical support rod	surface finish: matt gray
Schoeps	T 5g- table stand	1,5 kg, surface finish: matt gray
Schoeps	TCg	small deskstand
Schoeps	TR 200 KC 2g- active table stand	height : 230 mm, surface finish: matt gray
Schoeps	windscreen B 20	Wind noise attenuation at 18 km/h with bullet microphones: 25 dB-A With supercardioid microphones: 26 dB-A Diameter 50 mm
Schoeps	windscreen B 5	close-speech guard, foam
Schoeps	windscreen W 20 R 1	windscreen with plastic basket
Schoeps	WKC 5g -Colette cable	5m
Schoeps	WSR ORTF LU	for ORTF with 2 * CCM 4, ambience recording, including Windjammer. Pro Set: - KS 10 U: Stereo-Mikrofonkabel, 10m, XLR-5F auf XLR-5M -AK SU/2U: Breakout-Kabel: XLR-5F auf 2 * XLR-3M
Sennheiser	windscreen for MKH 60	incl. windjammer

Manufacturer	Item	Description
Sennheiser	windscreen for MKH 70	incl. windjammer
Sennheiser	Windshield for SKM 5000	
Sennheiser	windscreen W 20 R 1	windscreen with plastic basket
sonoVTS	Screen Floor Stand	
SONOVTS	Speaker holder for flight case	
TRED	Speaker/Light stand with "TV" spigots	
Vinten	Portable Pump	incl. mount for studio pedestals
PA Speaker		
Bose	502 BE Subwoofer	-Frequency Response (+/-3 dB)150 Hz - 140 Hz -Frequency Range (-10 dB)145 Hz - 160 Hz -Nominal DispersionOmni-directional below 200 Hz -Loudspeaker EQRequiredOverload Protection7-ampre AGC or 3AG (Littlefuse) -Long-Term Power Handling 450 W (1800 W peak) -Sensitivity (SPL / 1 W @ 1 m) 90 dB -SPLMaximum SPL @ 1 m4116 dB SPL (122 dB SPL peak) -Nominal Impedance 8 Ω
Bose	802 II Speaker	2-way speaker system, biamp / fullrange, 4x1/2", 120°x80°, 120 dB
EAW	JF 260 Speaker	2-way speaker system, biamp / fullrange, 1x12", 1x1,4", 500 watt, 60° x45°, 130 dB
EAW	JF 80 Speaker	2-way speaker system, 2x6,5", 1x1", 460 watt, 100°x80°, 126 dB
EAW	SM 200i Speaker	floor monitor, biamp / fullrange, 1x12", 1x1", 500 Watt, 90°, 131 dB
JBL	Control 1 Speaker	2-way speaker system, 5 1/4", 3/4", 150 watt, Speakon Ultra-compact two-way loudspeaker Magnetically shielded drivers allow placement next to a PC monitor / TV Suitable for wall mounting (swivelling wall brackets included) Splash-proof, for installation even in damp rooms or outdoors (do not expose to direct moisture)
Meyer Sound	M1D	UltraCompact Curvilinear Array Speaker
Meyer Sound	MM4 Speaker	The MM-4 is an extremely small, wide dispersion loudspeaker for system applications requiring high quality. Unlike conventional low voltage systems based on 70 volt transformers, the MM-4 connects directly to the amplifier and can therefore produce a higher level (110 dB maximum SPL) with dramatically reduced distortion. The elimination of transformers also simplifies large installations. Frequency response (Hz): 120 Hz - 18 kHz Dimension: 102mm x 102mm x 107mm Active/Passive: Passive
Meyer Sound	UPA-1P Speaker	2-way speaker system, 1x12", 1x3", 100°x40°, 133 dB, self-powered. Dual amplified by an integral two-channel category AB/bridged amplifier with complementary MOSFET power amplifiers. Maximum output is 700 watts or 350 watts per channel. Phase-corrected electronics provide flat phase and amplitude response, with exceptional impulse response and accurate imaging as a result. The UPA-1P also incorporates Meyer Sound's intelligent AC power system, which automatically preselects the correct voltage,
Meyer Sound	UPM-1P Speaker	selfpowered speakers in case with MYA-UPM rigging frames LF 2 x 5" & HF 1" 100° x 100° SPL max 123 dB
Meyer Sound	USW-1P	subbass 2x15", 135 db, self-powered

Manufacturer	Item	Description
Camera - Tripods - Pedestals -		
	Orbiter 500 superflat 2.0	(without head)
	Orbiter 500HD ultraflat	normal (without head)
Autoskript	Teleprompter BDL	19 " Teleprompter System: TFT ON Camera Unit, X-Box.
Grass Valley	Grass Valley LDK 5031/10 camera plate	LDK 5031/10 camera plate
Grass Valley	Camera Script Holder	Easy to attach and use Integrated reading light Attaches to a camera
Optio cycle		
Sachtler	Dolly XL-EFP-2	Rolling Base EFP 2
Sachtler	Dolly XL-OB2000	Rolling Base OB2000
Sachtler	EFP 2CF	Tripod, load 12-85 kg
Sachtler	OB 2000 XL	EFP- Tripod (without rolling base)
Sachtler	Pedestal C2 Set	
Sachtler	Vario Ped 2-75+	semi Pedestal with two-stage lifting column (incl. high-pressure air pump), incl. 6 x balancing weights
Sachtler	Video 25 Fluid Head	Fluid Head
Sachtler	Video 60plus	Fluidhead
Sachtler	Video 75 Fluid Head	Fluid Head, load 12-85 kg
Sachtler	Video 75plus V	Fluidhead with arms and wedgeplate
Sachtler	Video 90	fluidhead
SKS	Osprey Luftpumpe	
	16bar	
Sony	VCT-14	Quick-Release Tripod Adapter for Sony camera
Vinten	Hawk	pedestal 61-149 cm
Vinten	HD-2 RW	tripod with rolling base
Vinten	Linde, gas cylinder	nitrogen 5.0
Vinten	Osprey Elite Studio	Pedestal plus Fluid Head
Vinten	Quartz	Pedestal
Vinten	Quattro OB	Pedestal, 50-150cm
Vinten	Teal	pedestal, 76 -130 cm
Vinten	VD-VIBO 80	Nitrogen valve kit, 0-80 bar
Vinten	Vector 700 head	
Vinten	Vector 75	Vinten Head
Vinten	Vector 750/HD2	Vector 750 with legs and rolling base
Vinten	Vision 250 tripod	
Power Amplifier - Accessories		
Bose	802 C Controller	system-controller
Bose	802 C II Controller	system-controller
Canford	Stereo Headphone Amp.	beltpack headphone preamp, 9V DC
Lake People	F84	4x 1in2 or 2 x 1in4 or 1x 1in8 distribution amp
Lake People	G3	headphone-preamp
Lake People	G8	headphone-preamp
Lake People	G96	2-ch. headphone-preamp
Lake people		- 2 balanced signal inputs via XLR - 2 stereo amplifier with independent volume and balance - Gain internally switchable to +8 / +20 dB - Each stereo amplifier with 1 headphone output on the front - Each stereo amplifier with additional output on 1/4 "stereo jack on the back

Manufacturer	Item	Description
Lake People	Phone-Amp G93	The Phone-Amp G93 is a stereo headphone amplifier, differentes to most comparable models it's internele operating voltage may be altered to match the specific needs of different headphones. 8-600 Ohm
Meyer Sound	MM4 Amp Power Amp	2-ch. power amp, QSC PL1.8 watt & controller
Midas	XL42 Dual Mic-Pre EQ from the XL4 desk	2 channel mic-pre amp
Neumann	N 48i-2	phantom-power unit, for 2 microphones
QSC	PL 1.4 power amp	2-ch. power amp, 2x700 Watt
QSC	PL 1.8 power amp	2-ch. power amp, 2x900 Watt
Shure	FP 11	portable microfon amplifier, 9V DC
Shure	FP 12	beltpack headphone preamp, batterie powered
Sound Devices	MM1	microphone pre-amp, batterie-powered, 48V phantom-power
Track ONE	MIC-AMP	
Track ONE		
Yamaha	4220	4-ch. amp, 4x150 watt
IT / KVM		
acer	CATCenter X2	
Adder	CATX-USB-DA	USB VGA compatible with ADDERView AVX series for computers with VGA, USB Resolution up to 1920 × 1200 no power required robust ABS housing
Adder	x200/r	KVM Hi Res VGA, USB keyboard and Mouse plus stereo audio CATx Extender. Support for two remote computers up to 300 Mtrs
CHERRY	W95	Keyboard PS2 black
Cisco	C3KX-NM-10G	
Cisco	C3KX-PWR-350WAC	
Cisco	C3KX-PWR-715WAC	
Cisco	Catalyst 2960-S Series PoE+	
Cisco	Catalyst C3750X-48P-S 48 PORT PoE IP	48 Anschlüsse - Ethernet, Fast Ethernet, Gigabit Ethernet - 10Base-T, 100Base-TX, 1000Base-T + 1 , Power over Ethernet
Cisco	Catalyst C3750X-48T-S 48 PORT Switch	48 Ports - Ethernet, Fast Ethernet, Gigabit Ethernet - 10Base-T, 100Base-TX, 1000Base-T + 1
Cisco	Cisco 8-Port Gigabit PoE switch	
CISCO		
Cisco		
FRITZ	Box 6810 LTE	
Gigabyte	BRIX GB-BRI5H-8250 Config Server	
Guntermann & Drunck	CATCenter NEO16	KVM Matrix Ports for 16 Workstation- and 64 Computer-modules
Guntermann & Drunck	CATCenter NEO4 KVM-Matrixswitch	KVM Matrix Ports for 4 Workstation- and 32 Computer-modules
Guntermann & Drunck	CATCenter NEO8	KVM Matrix Ports for 8 Workstation- and 32 Computer-modules
Guntermann & Drunck	CATCenter X2	
Guntermann & Drunck	CATpro2-Audio-USB	
Guntermann & Drunck	CATpro2-DVI-Audio-UC-USB	DVI / Audio / USB - Dongle The computer module CATpro2 connects the external computer interfaces keyboard, video, mouse and audio with the CATCenter NEO system. It merges the appropriate signals, prepares them and routes them via CAT cable to the KVM matrix switch.
Guntermann & Drunck	CATpro2-PS/2 Computer modules	PS/2 KVM-Dongle, Connectivity for 1 CATCenter-Cluster The computer modules CATPro2 connect the external computer interfaces keyboard, video, mouse and audio with the Catcenter Neo. The corresponding signals are combined by the computer modules, processed and forwarded via CAT-X cable to the Catcenter Neo system.

Manufacturer	Item	Description
Guntermann & Drunck	CATpro2-UC-PS/2	PS/2 KVM-Dongle, Connectivity for 2 CATCenter-Cluster CATpro2 computer modules connect the computer's external keyboard, video, mouse, and audio interfaces with the CATCenter NEO system.
Guntermann & Drunck	CATpro2-UC-USB	USB KVM-Dongle, Connectivity for 2 CATCenter-Cluster
Guntermann & Drunck	CATpro2-USB	USB KVM-Dongle
Guntermann & Drunck	CATVision MC2-CON	
Guntermann & Drunck	CATVision MC2-CPU	
Guntermann & Drunck	CATVision-CON-RM Workplacemodul	KVM-Extender-System CATVision workplace - end (Receiver). Uncompressed transmission via CAT-x-Cable (x = 5, 6, 7) up to 300 m.
Guntermann & Drunck	CATVision-CPU-RM KVM Extender	KVM-Extender-System CATVision Computer - end (Transmitter). Uncompressed transmission via CAT-x-Cable (x = 5, 6, 7) up to 300 m.
Guntermann & Drunck	DiSign-CON-AV2-ld	
Guntermann & Drunck	DiSign-Splitter 1AV8	
Guntermann & Drunck	DL-Vision (M/S) -MC2-CON	KVM-Extender-System , Arbeitsplatzmodul (Empfänger) , Übertragung über Lichtwellenleiter (2 Fasern)
Guntermann & Drunck	DL-Vision (M/S) -MC2-CPU	KVM-Extender-System , Rechnermodul (Sender), Übertragung über Lichtwellenleiter (2 Fasern)
Guntermann & Drunck	DP 1.2-Vision con	
Guntermann & Drunck	DP-CPU	
Guntermann & Drunck	DVI-CON	The DVI-CON workstation modules are connected to the central module via CAT or fiber cables and provide the necessary interfaces for peripheral devices (monitor, keyboard, mouse, loudspeaker / microphone).
Guntermann & Drunck		
Guntermann & Drunck	Rack Console 17"	17" TFT-Tastatur-Schublade
		DVI + VGA
Guntermann & Drunck	UCON-s	Workstation-End-Module with Aux-Input
Hewlett Packard	Proliant DL120 G7 Server	1 RU Server, Win7 Eng. Inc 2x RAID IN 1 250GB SATA HPL ETY HDD 7200RPM
Imagine	MAG-SVR MAGELLAN CENTRAL CONTROLLER	1RU Magellan controller with redundant, 6 Ethernet ports, and 9 serial ports.
Lenovo	Tablet	incl. "VSMPANEL" Software
Lenovo	Think Pad 2	10" Touch Screen , Windows 8, incl. "PADdock" Dockingstation
Lenovo	ThinkCentre M71e	PC Win 7 Professional.
lenovo	ThinkPad	Riedel Director, Imagine Navigator, Imagine Z-Configurator etc...
Lenovo	ThinkPad Config PC	PC Win10 Professional.
Lenovo	ThinkPad, Windows 7 Eng	3,2G 8GB SYST 1TB 15,6IN W7P64 DVDRW GR 20AV006XGE
Lindy	USB CAT5 Extender	
Logitech	Keyboard GER K120	Keyboard USB black
Logitech	Keyboard UK K120	USB KEYBOARD BLACK (UK)
Logitech	Mouse PS2 optical RX250	Opical USB/PS2 Mouse white
Logitech	USB Mouse Optical	Opical USB Mouse black
Netgear	GS750E	Switch 48 Port Gigabit Ethernet LAN Switch Plus with 2x SFP (managed with IGMP, QoS and VLAN, desktop or 19 inch rack mounting)
Netgear	GS752TP - 100EUS	48 Port Gigabit Ethernet LAN PoE Switch Smart and 4x 1G-SFP (Network Switch Managed with 48x PoE + 380W, desktop or 19 inch rack mounting)
Netgear	GSM7224P-100NES (ProSafe)	GSM7224P is a rack-mount switch with 24 Gigabit ports. PoE
Netgear	JGS524E	Plus Switch 24 Port Gigabit Ethernet LAN Switch (desktop or 19 inch rack mounting, managed with IGMP Snooping, QoS and VLAN, fanless metal housing)
Netgear		24 Port 10/100 Mbps Fast Ethernet Switch

Manufacturer	Item	Description
--------------	------	-------------

Netgear		Gigabit Ethernet "Short-Reach" -Glasfaser connectivity LC duplex connector Compatible with SFP connectors all fully managed switches. Compatible with SFP connectors all Smart Switches. Compatible with SFP connectors of JGS524F. Provides Gigabit networks at distances of up to 1,000 m above laser-optimized OM4 multimode fiber cable with 50/125 microns. Provides Gigabit networks at distances up to 550 m over laser-optimized OM3 multimode fiber cable with 50/125 microns. Provides Gigabit networks at distances up to 275 m above laser-optimized OM3 multimode fiber cable with 50/125 microns.
Netgear	Switch 16port	
sonoVTS	Config PC	Config PC
sonoVTS	Config PC	
Versch. Hersteller	16 Port Gigabit/Fast Ethernet Switch	
Versch. Hersteller	24 Port Gigabit/Fast Ethernet Switch	
Versch. Hersteller	48 Port Ethernet Switch	48 Port Gigabit/Fast Ethernet Switch
Versch. Hersteller	8 Port Gigabit/Fast Ethernet Switch	

Adapter		
---------	--	--

Canford		
Cordial		
Cordial	MY - Auflösungskabel für Yamaha 25p auf XLR digital	
Diverse		
Diverse		
Diverse		
Diverse		
Diverse		
Diverse		
Diverse		
Diverse		
Diverse		
g d	No items available at the moment	
Grass Valley	Lemo-NL / D&H f/f	Triax-Adaptercable, Lemo/D&H female/ female
Grass Valley	Lemo-NL / D&H m/m	Triax-Adapterkabel, Lemo/D&H male/ male
Grass Valley	LemoUK/ D+H m/f	Triax-Adapter cable, UK/ D+H male/ female
Grass Valley	LemoUK/ D+H F/M	Triax-Adapterkabel, UK-Lemo/D+H male/ female
Grass Valley	LemoUk/Fischer f/f	Triax-Adapterkabel, UK/ Fischer fem./ fem.
Hosa	ainch cable	
Hosa		
Hosa		
Hosa		
Hosa	ainch cable	
Hosa	cinch cable	
Neutrik	NADITBNC-F	XLR female / 110Ω - BNC /75Ω AES Adaptor
Neutrik	NADITBNC-M	XLR male / 110Ω - BNC /75Ω AES Adaptor
Neutrik	speakon-NL4MM-connector	
Neutrik	speakon-NL4MM-connector	
Neutrik	Speakon-NL4MM-connector	
Neutrik	Speakon-NL8MM-connector	
Neutrik	speakon-NL8MM-connector	
Neutrik	XLR f - jack 1/4" balanced	adapter
Neutrik	XLR f - bodge plug	adapter
Neutrik	XLR f - cinch f	adapter
Neutrik	XLR f - f	adapter
Neutrik	XLR f - jack 1/4" balanced	adapter
Neutrik	XLR f - Jack 1/4" unbalanced	adapter

Manufacturer	Item	Description
Neutrik	XLR f - jack 1/4" balanced	adapter
Neutrik	XLR f - jack 1/4" balanced	adapter
Neutrik	XLR m - bodge plug	adapter
Neutrik	XLR m - cinch f	adapter
Neutrik	XLR f - jack 1/4" balanced	adapter
Neutrik	XLR f - jack 1/4" unbalanced	adapter
Neutrik	XLR f - jack 1/4" balanced	adapter
sono	adaptercable 25pol Sub-D - 30pol ML	for DA-88
sono	adaptercable Siemens - TRS jack	
sono		
sono	speakon- "in series-connection"	
sono	speakon- "in series-connection"	
sono	multipin fanout, 30-pin f - TT phone	adapter for Siemens-type connectors
sono	speakon- "in series-connection"	
sonoVTS	speakon- "in series-connection"	
sonoVTS	speakon- "in series-connection"	
sonoVTS	speakon- "in series-connection"	
sonoVTS	adaptercable for 1046 splitoutput	25 pin Sub-D / 8 x XLR
sonoVTS	adaptercable TRS-XLR f	balanced , 2m
sonoVTS	adaptercable TRS-XLR m	balanced , 2m
sonoVTS	multipin fanout, 30-pin f - TRS jack	
sonoVTS	multipin fanout, 30-pin M - TT phone	
sonoVTS	multipin fanout, 30-pin f - TT phone	adapter for Siemens-type connectors
sonoVTS	attenuator-adapter	
sonoVTS	speakon-XLR-adapter	
SONOVTS	speakon-multicore-split adapter	
sonoVTS	Y-cable , parallel-adapter XLR	
sonoVTS	Speakon-XLR-adapter	

Personnel

sonoVTS	video engineer, daily rate	10 hour /day. excl. Hotel / per diems / flight
sonoVTS	video technician, daily rate	10 hour /day
sonoVTS	commentary technician, daily rate	10 hour /day
sonoVTS		
sonoVTS	soundengineer, daily rate	10 hour /day
sonoVTS		
sonoVTS	intercom systemengineer, daily rate	10 hour /day
sonoVTS		
sonoVTS	assistent, daily rate	10 hour /day
sonoVTS	assistent, daily rate	10 hour /day
sonoVTS	soundengineer PA/FoH, daily rate	10 hour /day
sonoVTS	sound technician, daily rate	10 hour /day
sonoVTS		
sonoVTS	soundengineer, daily rate	10 hour /day
sonoVTS		
sonoVTS	transport	per km, one way
sonoVTS	intercom technician, overtime hour	overtime hour
sonoVTS	intercom technician, overtime hour	overtime hour
sonoVTS		
sonoVTS	soundengineer , overtime hour	overtime hour
sonoVTS		
sonoVTS	sound technician, overtime hour	overtime hour
sonoVTS		
sonoVTS	soundengineer PA/FoH, overtime hour	overtime hour
sonoVTS	chief engineer, daily rate	10 hour /day

Manufacturer	Item	Description
Utilities		
	Batterie 1,5V-AA Size	
	DAT Cassette 120 min	
	DAT Cassette 60 min	
	DAT Cassette 90min	
	Gaffa-Tape	
	Hi 8 Cassette DA 88 unformatted	
	Hi 8 Cassette DA 88 preformatted	
	Minidisk	
Diverse	Batterie 9V-Block	
Panasonic	Batterie 1,5V-AA Size	
Shure	Gaffa-Tape	
sono	BNC 1HE 20x	
Tesa		
Cables - mains/power-Accessories		
	euro power cord	
APC		Smart-UPS 750 VA Uninterruptable power source.
Apsa	power-distribution, 10-sockets	
Apsa	power-distribution, 10-sockets	
Apsa	power-distribution, 3-sockets	
Apsa	power-distribution, 5-sockets	
Apsa	power-distribution, 6-sockets	
Apsa	power-distribution, 8-sockets	
Apsa	power-distribution, 8-sockets	
Apsa	power-distribution, 10-sockets	
Bachmann	19" power strip 9x socket 1U	The Bachmann socket strip 333.401 is a 19 inch PDU socket unit with 1U aluminum profile for power distribution in the data center and use in the IT server rack. The power distribution unit contains nine protective contact sockets and a 1.8 m lead with 1.50 mm ² and angled plug.
Bachmann	Power strip 6x	Power strip, screwable, with 6 sockets, socket inserts turned by 45°, material: PVC color: white connection cable: 1,5m H05VV-F 3G1,5qmm
Bela	32A 5pin, 9 x schuko	seperate fuse for outlets
Bluebell	Shax Camera SC	Camera SMPTE 304M <-> SC - Dark Fiber Interface, Camera - End
Bluebell	Shax CCU SC	CCU SMPTE 304M <-> SC - Dark Fiber Interface, CCU - End
Canford	MDU6SF AC	Mains Distribution 1/12
Connex	19" SV 63A	
Connex		
Connex		
Connex	32A/3-Phasen -Kabel 5m	
Connex		
Connex	CP-G16-005 cabel	
Connex		
Connex	cPot CP-BV	
Connex	PWM-304 3HE	
Connex	PWM-304	
Connex	PWM-308 6HE	
Connex	SA 19" SV 32A	
Draka	SMPTE 311 / Lemo / 3m	SMPTE 311 Cable 3m / Lemo Connectors
Draka	SMPTE 311 / Lemo / 20m	SMPTE 311 Cable 20m / Lemo Connectors
Draka	SMPTE 311 / Lemo / 300m drum	SMPTE 311 Cable 300m / Lemo Connectors
Draka	SMPTE 311 / Lemo / 300m	SMPTE 311 Cable 300m / Lemo Connectors

Manufacturer	Item	Description
Draka	SMPTE 311 / Lemo / 40m drum	SMPTE 311 Cable 40m / Lemo Connectors
Draka	SMPTE 311 / Lemo / 100m	SMPTE 311 Cable 100m / Lemo Connectors
Draka	Triflex 8 / D+H /100m	Triax Cable 100m / Damar+Hagen Connectors
Draka	Triflex 8 / D+H /300m	Triax Cable 300m / Damar+Hagen Connectors
Eltepro	mains-cabledrum 2,5qmm, 33m	2,5qmm, 33m
Gifas		
Gifas	32A/3-phase, 6x 16A schuko	seperate fuse for outlets
Gifas	32A CEE, 2x schuko	seperate fuse for outlets
Gifas		
Gifas		
Gifas	32A/3-phase, 3x 32A CEE	pigtail, 3m
Gifas	32A/3-phase, 6x 16A schuko with loopthru, 32A/3-phase	seperate fuse for outlets
Gifas	63A/3-phase, 3 x schuko + 2 x 32A 5pol	seperate fuse for outlets
Grass Valley	Fischer/D+H m/m	Triax-Adapterkabel F/D male/male
Grass Valley	Fischer/D+H-f/f	Triax-Adaptercable F/D fem./fem
Grass Valley	Fischer/D+H-f/f	Triax-Adapter F/D fem./fem
Grass Valley	Fischer/D+H-m/m	Triax-Adapter F/D male./male
LiteFuze		
Neutrik	CONNEX PVT3S25-001	
Neutrik	CONNEX PVT3T25-001	
Neutrik	NAC3 FX Powercon cable 10m	
Neutrik	NAC3 FX Powercon cable 15m	
Neutrik	NAC3 FX Powercon cable 2,5m	
Neutrik	NAC3 FX Powercon cable 20m	
Neutrik	NAC3 FX Powercon cable 5m	
sono		
sono		
sono		
sono	power extension cord, 5m	Schuko - connector
sono	power extension cord, 10m	
sono	power extension cord, 20m	
sono	power extension cord, 20m	Schuko - connector
sono	power extension cord, 5m	
sono	power extension cord, 5m	
sono		
SONOVTS		
SONOVTS		
SONOVTS	32A/1-phase extension 15m	CEE connector
SONOVTS		
SONOVTS	32A/3-phase extension 15m	5pin CEE connector
SONOVTS		
SONOVTS	CEE 32A/1-phase extension 300m drum	CEE connector
SONOVTS		
SONOVTS	mains-cabledrum 2,5qmm, 33m	2,5qmm, 33m
Sony	HDFX-100/UF Triax Fibre Converter Kit for CCU	Fibre SMPTE/HD Triax Converter
Sony	HDTX100 Fibre-Triax Adaptor	HD Triax /Fibre SMPTE Converter

Manufacturer	Item	Description
Fiber - Cables - Accessories		
Fiberfox	fiber-optic cable MIL, 250m	Fiber cable, 250m FIBERFOX LWL MIL Cabel 4x50/125µm TD -04G50-3GB1GC-MIL, 600/600MHz, Connector: FIBERFOX EBC54-C-MM, Multimode
Fiberfox	LWL-Connector plug-in Modul MM	19" 1U frame FCM-FR/4-19, approx. 194mm deep. Front side: EBC54 built-in socket multimode 4 channel with protective cap recessed 45°, rear side: 2x SC-Duplex MM coupling with protective cap, only in combination with Fiberfox cable drum
Fiberfox	LWL-Connector	Interface EBC54 to SC Duplex
Fiberfox	LWL -Cable drum MIL, 500m Singlemode	FIBERFOX optic cable (PUR, halogenfree)single mode connector: FIBERFOX EBC54-C-SM
Imagine	ODS6800+CL8D Demux Modul	Passive eight channel optical de-mux 1271-1451 nm
Imagine	OMS6800+CL8D Mux Modul	OMS6800+CL8D Passive 8-channel optical mux 1271-1451 nm
Lynx	Yellobrigk OBD 1510 E Ethernet to Fiber Bidirectional Transceivers	1Gbit/S Ethernet Bidirectional Tansceiver
Lynx	Yellobrigk SFP OH TR 4 1270nm	Dual, single-mode Optical Transceiver (TX/RX) SFP Module 1270nm LC connectors dual
Lynx	Yellobrigk SFP OH TX 4 1310nm	Single-mode optical Transmitter (TX) SFP Module 1310nm LC connector
Lynx	Yellobrigk SFP OH TX 4 1330nm	Single-mode optical Transmitter (TX) SFP Module 1330nm LC connector
Lynx	Yellobrigk SFP OH TX 4 1350n	Single-mode optical Transmitter (TX) SFP Module 1350nm LC connector
Lynx	Yellobrigk SFP OH TX 4 1370n	Single-mode optical Transmitter (TX) SFP Module 1370nm LC connector
Lynx	Yellobrigk SFP OH TX 4 1610n	Single-mode optical Transmitter (TX) SFP Module 1610nm LC connector
Neutrik	OpticalCon Quad 100m	100m quad - singlemode Fiber with Neutrik OpticalCon Connectors
Neutrik	OpticalCon Quad 300m	300m quad - singlemode Fiber with Neutrik OpticalCon Connectors
Neutrik	OpticalCon Quad 400m	400m quad - singlemode Fiber with Neutrik OpticalCon Connectors
Neutrik	OpticalCon Quad Breakout Box	4 way singlemode Fiber breakout Box. LC APC (OpticalCon Quad - End) to LC / SC / E2000..... please specify at order
Neutrik	OpticalCON QUAD coupler (adapter) for cable extensions.	Fiber barrel
Opticis		RX and TX DVI<->Fiber Extends uncompressed WUXGA(1920x1200) 60Hz DVI signal up to 500 meters 1x multi-mode fiber SC. Auto-EDID management
Opticis	M1-201SA	DVI <-> Fiber Adapter 2x LC Multimode
Opticis	M1-201 SA	DVI <-> Fiber Adapter 4x LC Multimode
sommer cable	XLR patchcord, <1m	
sommer cable	XLR patchcord, <1m	
sommer cable	XLR patchcord, <1m	
sommer cable	XLR patchcord, <1m	
sono	microphone cable, 10m	neutrik XLR-connectors
sono	Speakon cable, 2-pair, <2m	
sono	Speakon cable, 2-pair, 2,5m	
sono	Speakon cable, 2-pair, 10m	
sono	Speakon cable, 2-pair, 15m	
sono	Speakon cable, 2-pair, 20m	
sono	Speakon cable, 2-pair, 25m	
sono	Speakon cable, 2-pair, 5m	
sono	Speakon cable, 4-pair, 10m	
sono	Speakon cable, 4-pair, 15m	
sono	Speakon cable, 4-pair, 30m	
sono	Speakon cable, 4-pair, 2,5m	
sono	Speakon cable, 4-pair, 20m	
sono	Speakon cable, 4-pair, 25m	

Manufacturer	Item	Description
sono	Speakon cable, 4-pair, 30m	
sono	Speakon cable, 4-pair, 30m	
sono	Speakon cable, 4-pair, 7,5m	
sono	Speakon cable, 8-pair, 10m	
sono	Speakon cable, 8-pair, 10m	
sono	Speakon cable, 4-pair, 20m	
sono	Speakon cable, 8-pair, 25m	
sono	XLR patchcord, 2m	
SONOVTS	4xLC 9/125 Glasfaser leichte Kabeltrommel 300m	
sonoVTS	AES-EBU XLR patchcord, 2,5m	
sonoVTS	AES-EBU XLR patchcord, 2,5m	Neutrik XLR-connectors
SONOVTS	fiber-optic cable MIL, 250m	LWL Cabel, 250m LWL MIL Kabel (PUR, FRNC) 4xsingle-mode, Connectors: LC
sonoVTS	HD2line OCWDM-SM-27-LC	Bi-directional mux/demux of up to 8 wavelengths in the 1270nm to 1430nm spectrum (ITU-T G.694.2 compliant), Expandable from 9 to 18 channel systems Passive design for any bit rate High optical isolation for low crosstalk
SONOVTS	microphone cable, 2-pair, drum 100m	Neutrik 5 pin XLR connector
SONOVTS	microphone cable, 2-pair, drum	Neutrik 5 pin XLR connector
SONOVTS	microphone cable, 2-pair, 100m drum	Neutrik 5 pin XLR connector
SONOVTS	microphone cable, 50m, drum	Neutrik XLR-connectors
SONOVTS	microphone cable, 100m, drum	Neutrik XLR-connectors
SONOVTS	microphone cable, 100m, drum	Neutrik XLR-connectors
SONOVTS	microphone cable, 75m, drum	Neutrik XLR-connectors
sonoVTS	microphone cable, 20m	Neutrik XLR-connectors
sonoVTS	microphone cable, 30m	Neutrik XLR-connectors
sonoVTS	microphone cable, 5m	Neutrik XLR-connectors
sonoVTS	OMUX CWDM 1270 - 1610 nm	Optical multiplexer/demultiplexer, lower und upper waveband, 2 x 9 Inputs / Outputs on LC wavelengths: 1270, 1290, 1310, 1330, 1350, 1370, 1390, 1410, 1430, 1450, 1470, 1490, 1510, 1530, 1550, 1570, 1590, 1610 nm
SONOVTS	Speakon cable, 4-pair, 50m	
SONOVTS	Speakon cable, 4-pair, 50m drum	
SONOVTS	Speakon multicore 25m	
SONOVTS	multipin fanout for Speakon multicore	
sonoVTS	XLR, 2 pair, 10m	
sonoVTS	XLR, 2 pair, 20m	
sonoVTS	XLR, 2 pair, 5m	
sonoVTS	XLR, 2 pair, 10m	
VIDI	Fibre Splitter 1>2 (12xLC > 1xMTP12, 12xLC)	1>2 (12xLC > 1xMTP12, 12xLC)
VIDI	Fibre Splitter 1>4 (MTP12 > 3xMTP12, 12xLC)	1>4 (MTP12 > 3xMTP12, 12xLC)
WGD	MTP Fiber cable 65m	
WGD	MTP Fiber cable 100m	
WGD	MTP Fiber cable 300m	
WGD	Compact Modul MTP-m/6xLC dupl 12E9/125µm	MTP to LC Modul
WGD	REDi-Way Compact Modul MTP-m/6xLC dupl 12E9/125µm	for up to 8 Modules 1U Rack Shelf for 8 Compact-Modules MTP to LC

Manufacturer	Item	Description
Video - Cables - Accessories		
ADC	HUM-1 Hum Eliminator	Humbucker HDSDI Video Hum Eliminator
ADC	PPI/PPE 1232-MVJT	The PPE1232-MVJT is a Pro Patch Enhanced video panel, 1 RU, black with 2 rows of 32 midsize jacks, MVJ-3 dual self-normalling super video with 75 Ohm termination. Colour black/silver
CANARE	32MD-ST	75ohm Mid Size Video Patchbay Available as EIA 2RU Size
CANARE	MVPC005	Patch Kabel 0,5m
CANARE	MVPC01	Patch Kabel 1m
Canford	BNC Termination Panel 1U, 1X24, 3G, 75 ohm, black	19" 1U with 24 HD-BNC Connectors these "High Definition" 75 ohm panels are intended for 3G and 1.5G high definition, standard definition and analogue video applications. The performance exceeds the requirements of SMPTE292M and SMPTE424M making them suitable for composite and component video, 270 Mb/s SDI and uncompressed 1080i or 1080p HD-SDI video up to 3Gb/s. They are supplied fully-populated with Canford insulated, double-sided, "High Definition", 75 ohm, BNC sockets, equally spaced across the panel. The 50 ohm type is recommended for analogue use only, see separate entries.
Canford	BNC Patch	1 U with 20 HD-BNC Connectors
sono	BNC cable	
sono	BNC, 10m	
sono	BNC, 20m	
sono	BNC, 5m	
sonoVTS	BNC Patch	1 U with 20 HD-BNC Connectors
sonoVTS	BNC, <5m	
SONOVTS	BNC, 30m	
SONOVTS	HDTV BNC cable, 100m, drum	cable specs: Draka 1.2L/4.8DZ - 75Ω HDTV
SONOVTS	HDTV BNC cable, 30m, drum	
SONOVTS	HDTV BNC Kabeltrommel, 50m 1.2/4.8	cable specs: Draka 1.2L/4.8DZ - 75Ω HDTV
SONOVTS	BNC cable, 200m, drum	cable specs: Draka 1.2L/4.8DZ - 75Ω HDTV
SONOVTS	HDTV BNC cable, 75m, drum	cable specs: Draka 1.2L/4.8DZ - 75Ω HDTV
Switchcraft	Patchcord BLK 2FT	Video Patchcord
Switchcraft	VPP24K1HDNNT	1RU, 2X24 Standard "HD" 3Ghz Video Bay, Non-Normalled / Non-Terminated
Switchcraft	VPP24K1HDNT	Videopatchfield 1RU, 2X24 Standard "HD" 3Ghz Video Bay, Normalled / Non-Terminated

LAN - Cables - Accessories		
FS	Fiber - Ethernet MediaConverter	A Pair of : 1310nm-TX/1550nm-RX 10km LC, Bi-Direktional on one Fiber. 2x 10/100/1000Base-T RJ45 to1x 1000Base-X SFP
SONOVTS	CAT5 cabel, 20m	
SONOVTS	CAT5 cabel, 2m	
SONOVTS	CAT5 cabel, 30m	
SONOVTS	CAT5 cabel, 3m	
SONOVTS	CAT5 cabel, 50m	
SONOVTS	CAT5 cabel, 5m	
SONOVTS	CAT7 leichte Kabeltrommel, 50m	
SONOVTS	Sat Antennenkabel leichte Kabeltrommel, 50	

Manufacturer	Item	Description
Cables - miscellaneous		
Clicktronic		
Diverse		
Hosa	cinch cable	
Mogami	TT-Phone patchcord	
sono	Misc. cables/adapters	for whole system
sono	RF-cable RG 213N-N, misc length	
sono	Cables / Adaptors / Accessories	for connecting the equipment
sono		
SONOVTS	multipin fanout, 54-pin f - 2x 30-pin	adapter for Siemens-type connectors
SONOVTS	multipin fanout, 54-pin f - XLR (CMU21)	adapter for commentators-box
SONOVTS	multipin fanout, 30-pin f - XLR f (blue)	adapter for Siemens-type connectors
SONOVTS	multipin fanout, 30-pin m - XLR f (yellow)	adapter for Siemens-type connectors
SONOVTS	multipin fanout, 30-pin M - XLR m (blue)	adapter for Siemens-type connectors
SONOVTS	multipin fanout, 30-pin m - XLR VTR	adapter for VTR, 5x XLR female/male
SONOVTS	multipin fanout, 54-pin f - 2x 30-pin	adapter for Siemens-type connectors
SONOVTS	multipin fanout, 30-pin f - XLR m (red)	
SONOVTS	multicore 24-pair, 100m, drum	ends on LK85 multipin connector, incl.breakoutboxes
SONOVTS	multicore 24-pair, 50m, drum	ends on LK85 multipin connector, incl.breakoutboxes
SONOVTS	multicore 10-pair, 10m	ends on Siemens connector
SONOVTS	multicore 10-pair, 20m	ends on Siemens connector
SONOVTS	multicore 10-pair, 30m	ends on Siemens connector
SONOVTS	multicore 10-pair, patch F-F	ends on Siemens connector
SONOVTS	multicore 10-pair, patch M-F, 1-3m	ends on Siemens connector
SONOVTS	multicore 10-pair, patch M-F, 5m	ends on Siemens connector
SONOVTS	multicore 10-pair, patch M-M	ends on Siemens connector
SONOVTS	AES / EBU multicore D110, 50m, drum	multicore AES / EBU, 50m, drum, Siemens connectors
SONOVTS	multicore 10-pair, 100m, drum	ends on Siemens connector
SONOVTS	multicore 10-pair, 150m, drum	ends on Siemens connector
SONOVTS	multicore 10-pair, 50m, drum	ends on Siemens connector
SONOVTS	stagebox universal	10xXLRf, 10xXLRm, 2xSiemens
SONOVTS	multicore 10-pair, 250m, drum	ends on Siemens connector
SONOVTS	stagebox 10 inputs	XLR male / female <-> Siemens connector
SONOVTS	stagebox 24 inputs	
SONOVTS	stagebox 24 inputs	
SONOVTS	stagebox 24inputs	
SONOVTS	Video Multicore, 6 cables BNC, 10m	
SONOVTS	Video Multicore, 6 cables BNC, 15m	
SONOVTS	Video Multicore, 6 cables BNC, 20m	
SONOVTS	Video Multicore, 6 cables BNC, 25m	
SONOVTS	Video Multicore, 6 cables BNC, 30m	
SONOVTS	Video Multicore, 6 cables BNC, 3m	
SONOVTS	Video Multicore, 6 cables BNC, 40m	
SONOVTS	Video Multicore, 6 cables BNC, 50m	
SONOVTS	Video Multicore, 6 cables BNC, 5m	
SONOVTS	Video Multicore Kabeltrommel 3-fach BNC 0.6/2.8, 60m	
sonoVTS		
the sssnake	Cat Snake 3FB	
the sssnake	Cat Snake 3MB	

Manufacturer	Item	Description
XX		

Hyperion	Office chair with ergonomic backrest with neck support (available as of October)	Relieving office chair, ergonomic shaping of backrest, headrest and seat surface Relieving armrests Elegant base with 5 double castors Maximum load capacity: 130 kg
----------	--	---

Tradeshaw Equipment

sonoVTS	Bag
sonoVTS	ball pen
SonoVTS	Brochure Stand
sonoVTS	Corporate Brochure
sonoVTS	Corporate Flag
sonoVTS	HDQLINE Brochure
sonoVTS	Lanyard
sonoVTS	Multi Panel Monitor Wall Tradeshow Edition 3x3
sonoVTS	Multi Panel Monitor Wall Tradeshow Edition 8x3
sonoVTS	OB Vehicles Brochure
sonoVTS	Rollup EQUIPMENT RENTAL
sonoVTS	Rollup HDQLINE
sonoVTS	Rollup SERVICE & CONSULTING
sonoVTS	Rollup WORLDWIDE BROADCASTING
sonoVTS	USB Stick (large)
sonoVTS	USB Stick (small)
sonoVTS	ZAEHL Brochure

DVB-T / DVB-C / DVB-S2

Anadol	HD 202c PLUS DVB-C / C2	
Humax	HD Kabel Receiver DVB-C	
Kathrein	LNB UAS 572	Universal twin feed system - 10.70-12.75 GHz - 2 switchable outputs (14/18 V, 0/22 kHz) - Current drain: 175 mA - Multi-feed compatible
Kathrein	Sat-Antenne CAS 80gr	Sat antenna 75 cm - Graphite - Powder coated aluminium reflector - Mast clamp: 38-90 mm, galvanised and coated steel - Tilting multi-feed mounting device

amptown		
amptown		
Arri		
D-Link	DGS-1008D	
Furman	AR 2306	power-conditioner 6A with AC-filter
Furman	AR 2330	power-conditioner 30A
Furman	PL Plus E	10A power-conditioner
Furman	PL-8 E	power-conditioner
Gaggia	Saeco Linie Gaggia Deco D Automatic	
König & Meyer		

Manufacturer	Item	Description
König & Meyer		
Lynx	C DA 5005	5 Ch. SDI to CVBS Converter
Midas	Quad-Panner	custom built for "Pink Floyd", real vintage
NTP	177-400	peakmeter
Peli		
Peli		
Peli		
Peli		
proCase		
Sennheiser		
sono		
SONOVTS		
sonoVTS	Norm-Lighting Control Unit	
sonoVTS	Norm-Lighting RGBW-Strip	
sonoVTS	stereo volume-control	balanced volume control, XLR in/out
Zarges		
Zarges		